

Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PermiNex® 2000 Series Resists
- · Article number: Y614022, Y614045, Y614058, Y614064
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

*Tel:* +44-0-1788-537535 *Fax:* +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

#### · 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

#### · Hazard-determining components of labelling:

Epoxy Resin M2

#### · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

*P273* Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

*P302+P352 IF ON SKIN: Wash with plenty of soap and water.* 

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

*P333+P313* If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

41.8 % of the mixture consists of component(s) of unknown toxicity.

Contains 59.2 % of components with unknown hazards to the aquatic environment.

(Contd. on page 3)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 2)

#### · 2.3 Other hazards

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 120-92-3	Cyclopentanone	15-75%
EINECS: 204-435-9	🐠 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	Epoxy Resin M2	5-25%
	Aquatic Chronic 2, H411; 🐠 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
	Epoxy Resin M3  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-10%
CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	<1.5%
EINECS: 219-784-2	� Eye Dam. 1, H318	
· Additional Compone	ents:	
D : , 1:0		15 50

· Additional Components:	
Proprietary modified epoxy resin	15-50%
Proprietary Photoacid Generator	<1.5%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 3)

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers:

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

(Contd. on page 5)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 4)

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Clear to light yellow

· Odour: Mild

• *Odour threshold:* Not determined.

(Contd. on page 6)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

	(Contd. of page
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 130°C
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower: Upper:	1.3 Vol % 0.0 Vol %
Vapour pressure at 20 °C:	11 hPa
Density: Relative density Vapour density Evaporation rate	Not determined See Other information Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
9.2 Other information	Name         Number         Sp. Grav.         VOC(%by wt.)         VOC(g/L)           PN 2001         Y614022         1.0018         70-75         710           PN 2005         Y614045         1.0619         40-45         445           PN 2010         Y614058         1.1020         25-30         290           PN 2015         Y614064         1.1220         15-20         190

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

(Contd. on page 7)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 6)

Corrosive gases/vapours

Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Epoxy Res	Epoxy Resin M2		
Oral	LD50	>2000 mg/kg (Rat)	
2530-83-8	2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8030 mg/kg (Rat)	
Dermal	LD50	4248 mg/kg (Rat)	
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)	
120-92-3 (	120-92-3 Cyclopentanone		
Oral	LD50	1820 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	19.5 mg/l (Rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

	12.1 Towery			
	· Aquatic toxicity: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane			
	LC50/96 h   55 mg/l (Cyprinus carpio (common carp))			
	EC50/48 h   30 mg/l (daphnia magna)			
	EC50/72 h   255 mg/l (Desmodesmus subscipatus (green algae))			
Ī	120-92-3 Cyclopentanone			
	LC50/48 hr 2950 mg/L (golden orfe)			
LC50/96 h $> 100 mg/l (fish)$		>100 mg/l (fish)		

(Contd. on page 8)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 7)

EC50/48 h 3600 mg/l (Ceriodaphnia dubia (water flea))

100 mg/l (daphnia magna)

EC50/72 h |>100 mg/l (scenedesmus subspicatus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION, MARINE POLLUTANT
14.3 Transport hazard class(es)	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance Formaldehyde, polymer with 1-chloro-2,3-epoxypropane as phenol



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

	(Contd. of page
Hazard identification number (Kemler code):	30
EMS Number:	F- $E$ , $S$ - $E$
Stowage Category	A
14.7 Transport in bulk according to Annex II o	nf .
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
- ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)

(Contd. on page 10)



Printing date 03.05.2023 Version number 5 Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 9)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GD -