

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

• Article number: M089025

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- **Product category** PC21 Laboratory chemicals
- · Application of the substance / the mixture Solvents

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Kayaku Advanced Materials, Inc.
200 Flanders Road
Westborough, MA 01581
Tel: (617) 965-5511
Fax: (617) 965-5818

- Further information obtainable from: Product Safety Email: productsafety@kayakuam.com
 1.4 Emergency telephone number: Kayaku Advanced Materials : 617,065,551
- Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

2 H351 Suspected of causing cancer.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU —



Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS0 · Signal word Danger · Hazard-determining components of labelling: Methyl isobutyl ketone Isopropyl alcohol · Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H351 Suspected of causing cancer. H336 May cause drowsiness or dizziness. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. *P301+P310* P302+P352 IF ON SKIN: Wash with plenty of soap and water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position *P304+P341* comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P337+P313 If eye irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Cont	td. of page 2
· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	Isopropyl alcohol Ø Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336	70-80%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4	Methyl isobutyl ketone Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l	20-30%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a
- considerable distance to a source of ignition and flash back along vapor trail.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.

(Contd. on page 4)

EU -



Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 3)

Ensure adequate ventilation • **6.2 Environmental precautions:** Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

• 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.

• Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

• Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

Store under lock and key and with access restricted to technical experts or their assistants only.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-10-1 Methyl isobutyl ketone

IOELV Short-term value: 208 mg/m³, 50 ppm

Long-term value: 83 mg/m³, 20 ppm

• *Additional information:* The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

EU -



Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 4)

Avoid contact with the eyes.

Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves PVA gloves

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection

Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

General Information Physical state	Liquid	
Colour:	Colourless	
Odour:	Like alcohol	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling po	int	
and boiling range	82-116 °C	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	1.7 Vol %	
Upper:	12.0 Vol %	
Flash point:	13 °C	
Auto-ignition temperature:	425 °C	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic:	Not determined.	
Solubility		
water:	Partly miscible.	
Partition coefficient n-octanol/wa	ter	
(log value)	Not determined.	

е б) — ЕН



Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Contd. of page
Vapour pressure at 20 °C:	43 hPa
Density and/or relative density	
Density:	Not determined.
2	Not determined
Relative density at 20 °C	$0.789 \ g/cm^3$
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Liquid
Important information on protection of	
health and environment, and on safety	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor
- • •	mixtures are possible.
Solvent content:	1
Organic solvents:	100.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical	
hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	, olu
Highly flammable liquid and vapour.	
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	, 010
flammable gases in contact with water	
Void Ouidiaina liauida	Vaid
Oxidising liquids	Void Void
Oxidising solids	Void Veid
Organic peroxides	Void Veid
Corrosive to metals	Void Veid
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Possible formation of peroxide.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

(Contd. on page 7)

⁻ EU ·

Printing date 12.05.2023

Safety data sheet according to 1907/2006/EC, Article 31

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 6)

Contact with incompatible materials. • 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Flammable gases/vapours

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-63-0 Isopropyl alcohol			
Oral	LD50	5045 mg/kg (Rat)	
	LD50	5045 mg/kg (Rat) 12800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (Rat)	

108-10-1 Methyl isobutyl ketone

Oral	LD50	2080 mg/kg (Rat)
Dermal		1600 mg/kg (rab)
Inhalative	LC50/4 h	100 mg/l (Rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

• *Reproductive toxicity Based on available data, the classification criteria are not met.*

- · STOT-single exposure
- May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

- *Experience with humans:* No further relevant information available.
- \cdot 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

•	12.	1	Toxicity
---	-----	---	----------

· Aquatic tox	icity:
67-63-0 Isoj	propyl alcohol
EC50/48 h	7550-13300 mg/l (daphnia magna) (immobilization)
EC50/72 h	>1000 mg/l (scenedesmus subspicatus) (Growth rate inhibition)
LC50/96 h	9640-10400 mg/l (Pimephales promelas)
	(Contd. on page 8)

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 12.05.2023

Printing date 12.05.2023

Version number 7 (replaces version 6)

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 7)

		(Contd. of page 7)
108-10-1	Methyl isobutyl ketone	
EC50/96 h	ur 980 mg/l (scenedesmus subs	picatus)
	400 mg/l (Selenastrum capri	icornutum)
LC50/24 h	5000 mg/l (daphnia magna)	
	460 mg/l (goldfish)	
LC50/96 h	505 mg/l (fathead minnow)	
	505-540 mg/l (Pimephales p	oromelas)
	600 mg/l (Salmo gairdneri)	
 12.5 Result PBT: Not vPvB: Not 12.6 Endo The produt 12.7 Other Additional General n Water haz 	applicable. crine disrupting properties ct does not contain substances r adverse effects l ecological information: otes: ard class 1 (German Regulatio	
· 13.1 Wast	ON 13: Disposal considerate treatment methods	tions
	be disposed together with house	chold garbage. Do not allow product to reach sewage system. th International, National, and regional regulations.
	l packaging: ndation: Disposal must be maa	le according to official regulations.
SECTIO	DN 14: Transport informa	tion
· 14.1 UN n · ADR, IMI	number or ID number DG, IATA	UN1993
	- · ·	
· ADR, IMI	roper shipping name DG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL, METHYL ISOBUTYL KETONE)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



3 Flammable liquids.

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Contd. of page
· Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
Transport/Additional information:	
ADR • Limited quantities (LQ) • Transport category • Tunnel restriction code	1L 2 D/E
UN ''Model Regulation'':	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANO (ISOPROPYL ALCOHOL), METHYL ISOBUTYL KETONE, 3, II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.05.2023

Version number 7 (replaces version 6)

Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Classification according to Regulation (EC) No 1272/2008
- Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.
- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- Revision History:
- The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.
- Version number of previous version: 6
- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity Category 4
- *Eye Irrit. 2: Serious eye damage/eye irritation Category 2*
- Carc. 2: Carcinogenicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3