

Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer
- · Article number: M089025
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC21 Laboratory chemicals
- · Application of the substance / the mixture Solvents
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

*Tel:* +44-0-1788-537535 Fax: +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

**Product Safety** 

Email: productsafety@kayakuam.com · 1.4 Emergency telephone number:

Kayaku Advanced Materials: 617-965-5511 Chemtrec USA Emergency: 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



H351 Suspected of causing cancer. Carc. 2

(Contd. on page 2)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 1)



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

· Signal word Danger

#### · Hazard-determining components of labelling:

Methyl isobutyl ketone

Isopropyl alcohol

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

*P337+P313 If eye irritation persists: Get medical advice/attention.* 

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

*P403+P235* Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

#### · Results of PBT and vPvB assessment

· **PBT**: Not applicable.

(Contd. on page 3)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 2)

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	Dangerous components:		
CAS: 67-63-0	Isopropyl alcohol	70-80%	
EINECS: 200-661-7	🔖 Flam. Liq. 2, H225; 💠 Eye Irrit. 2, H319; STOT SE 3, H336		
CAS: 108-10-1	Methyl isobutyl ketone	20-30%	
EINECS: 203-550-1			

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 3)

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

*Ensure adequate ventilation.* 

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

Store under lock and key and with access restricted to technical experts or their assistants only.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

### 67-63-0 Isopropyl alcohol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

(Contd. on page 5)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 4)

### 108-10-1 Methyl isobutyl ketone

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

Sk, BMGV

### Ingredients with biological limit values:

#### 108-10-1 Methyl isobutyl ketone

BMGV 20 µmol/L

Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves PVA gloves
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Colourless

(Contd. on page 6)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Contd. of page
Odour:	Like alcohol
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 82-116 °C
Flash point:	13 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	12.0 Vol %
Vapour pressure at 20 °C:	43 hPa
Density:	Not determined.
	Not determined
Relative density at 20 °C	$0.789 \text{ g/cm}^3$
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Partly miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Possible formation of peroxide.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

· 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

(Contd. on page 7)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 6)

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide Flammable gases/vapours

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	· LD/LC50 values relevant for classification:		
67-63-0 Is	67-63-0 Isopropyl alcohol		
Oral	LD50	5045 mg/kg (Rat)	
Dermal	LD50	12800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (Rat)	
108-10-1 N	108-10-1 Methyl isobutyl ketone		
Oral	LD50	2080 mg/kg (Rat)	
Dermal	LD50	1600 mg/kg (rab)	
Inhalative	LC50/4 h	100 mg/l (Rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eve irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: No further relevant information available.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

_	· 12.1 10xicuy		
	· Aquatic toxicity:		
	67-63-0 Isopropyl alcohol		
	EC50/48 h   7550-13300 mg/l (daphnia magna) (immobilization)		
	EC50/72 h	>1000 mg/l (scenedesmus subspicatus) (Growth rate inhibition)	
	LC50/96 h	9640-10400 mg/l (Pimephales promelas)	
	108-10-1 Methyl isobutyl ketone		
	EC50/96 hr 980 mg/l (scenedesmus subspicatus)		
		400 mg/l (Selenastrum capricornutum)	

(Contd. on page 8)



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

7)

		(Conta. of page /)
LC50/24 h	5000 mg/l (daphnia magna)	
	460 mg/l (goldfish)	
LC50/96 h	505 mg/l (fathead minnow)	
	505-540 mg/l (Pimephales promelas)	
	600 mg/l (Salmo gairdneri)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name · ADR, IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHO) METHYL ISOBUTYL KETONE)
14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· ADR, IMDG, IATA	
· ADR, IMDG, IATA · Class	3 Flammable liquids.
	3 Flammable liquids.
Class	<u> •</u>
· Class · Label	<u> •</u>
Class Label 14.4 Packing group	3



Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Contd. of page 8
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANO) (ISOPROPYL ALCOHOL), METHYL ISOBUTYL KETONE), 3 II

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 10)





Printing date 12.05.2023 Version number 7 Revision: 12.05.2023

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 9)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3