

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** eTECTX Series Resists
- **Article number:** eTECTX 1010, eTECTX 1050, eTECTX 1075
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Sector of Use** SU16 Manufacture of computer, electronic and optical products, electrical equipment
- **Application of the substance / the mixture** Photoresist
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Further information obtainable from:**
 Product Safety
 Email: productsafety@kayakuAM.com
- **1.4 Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300 (24 hr)
 Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07 GHS08 GHS09

· Signal word *Warning*

· Hazard-determining components of labelling:

Proprietary Epoxy Resin

Proprietary epoxy resin M1

Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains 32.7 % of components with unknown hazards to the aquatic environment.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

EU

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** Mixture: consisting of the following components.

· Dangerous components:

	Proprietary Epoxy Resin STOT RE 2, H373; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 4, H413	25-50%
	Proprietary epoxy resin M1 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9 Reg.nr.: 01-2119495595-21-0000	Cyclopentanone Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-40%
CAS: 108-32-7 EINECS: 203-572-1 Index number: 607-194-00-1	Propylene carbonate Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
CAS: 89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	1-5%
CAS: 71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	1-5%

· Additional Components:

	Proprietary Resin Modifier	5-10%
	Epoxy Compound Eye Dam. 1, H318	<1%
CAS: 96-48-0 EINECS: 202-509-5	gamma-Butyrolactone Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H336	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - Alcohol resistant foam
 - Fire-extinguishing powder
 - Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:**
 - Water with full jet
 - Water
- **5.2 Special hazards arising from the substance or mixture**
 - Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Keep away from ignition sources.
 - Ensure adequate ventilation
- **6.2 Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaust at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:**
 Store in a cool location.
 Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
- **Information about storage in one common storage facility:**
 Do not store together with oxidising and acidic materials.
 Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed containers.
 Protect from heat and direct sunlight.
 Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**
 The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from food and beverages.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Clear to light yellow
Odour:	Sweetish
Odour threshold:	Not determined.

· pH-value:	Not determined.
-------------	-----------------

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	130 °C

· Flash point:	30 °C
----------------	-------

· Flammability (solid, gas):	Not applicable.
------------------------------	-----------------

· Ignition temperature:	430 °C
-------------------------	--------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
------------------------------	------------------------------

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-------------------------	---

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure:	Not determined.
--------------------	-----------------

· Density:	Not determined
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
---	-----------------------------------

· Partition coefficient: n-octanol/water:	Not determined.
---	-----------------

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic polymerisation.
- **10.4 Conditions to avoid**
 Heat, flames and sparks. Extremes of temperature and direct sunlight.
 Contact with incompatible materials.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**
 Carbon monoxide and carbon dioxide
 Danger of forming toxic pyrolysis products.
 Corrosive gases/vapours
 Antimony oxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:
Proprietary epoxy resin M1

Oral	LD50	>2000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (Rat)

Epoxy Compound

Oral	LD50	8030 mg/kg (Rat)
Dermal	LD50	4248 mg/kg (Rat)
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)

Proprietary Epoxy Resin

Oral	NOEL 28 day repeated dose	250 mg/kg/day (Rat)
------	---------------------------	---------------------

120-92-3 Cyclopentanone

Oral	LD50	1820 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)

Proprietary epoxy resin M1

Oral	LD50	>2000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (Rat)

108-32-7 Propylene carbonate

Oral	LD50	>29000 mg/kg (Rat)
Dermal	LD50	>20,000 mg/kg (rabbit)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 7)

· **Specific symptoms in biological assay:**

Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol] CAS 28906-06-9: This material was mutagenic in the Ames bacterial assay and showed a positive result in a mammalian cell chromosomal aberration test.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (CAS 2530-83-8):

This material was weakly mutagenic in the Ames test, mouse lymphoma assay, and an in vitro sister chromatid exchange test; however results of in vivo genotoxicity studies have shown mixed results. Repeated exposure of rats or rabbits to this material did not result in an increase in sister chromatid exchange, while single exposures of mice to a hydrosylate of this materials resulted in a significant increase in micronucleated polychromatic erythrocytes. The potential relevance to humans is unknown; however, it is unlikely that this material presents a significant genotoxic hazard, in that it lacks any local tumorigenic response the the chronic recurrent application to mouse skin.

Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol] CAS 28906-96-9:

This material was mutagenic in the Ames bacterial assay and showed a positive result in a mammalian cell chromosomal aberration test.

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

· **Experience with humans:** No further relevant information available.

· **Additional toxicological information:**

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

LC50/24 h 4.4 mg/l (daphnia)

LC50/48 hr 0.68 mg/L (daphnia)

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

LC50/24 h 4.4 mg/l (daphnia)

LC50/48 hr 0.68 mg/L (daphnia)

Epoxy Compound

EC50/48 h 30 mg/l (daphnia magna)

EC50/72 h 255 mg/l (Desmodesmus subscipatus (green algae))

LC50/96 h 55 mg/l (Cyprinus carpio (common carp))

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 8)

120-92-3 Cyclopentanone

EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/48 hr	2950 mg/L (golden orfe)
LC50/96 h	>100 mg/l (fish)

Proprietary Epoxy Resin

LC50/96 h	>0.31 mg/l (algae)
	>0.31 mg/l (Water flea)
NOEC/96 h	≥0.99 mg/l (algae)

108-32-7 Propylene carbonate

EC50/17 h	>10000 mg/l (Pseudomonas putida)
EC50/48 h	>500 mg/l (daphnia magna)
EC50/72 h	>500 mg/l (scenedesmus subspicatus)
LC50/96 h	2200 mg/l (Leuciscus idus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Disposal must be made in accordance with International, National, and regional regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1866

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 9)

· 14.2 UN proper shipping name	RESIN SOLUTION
· ADR, IATA	RESIN SOLUTION, MARINE POLLUTANT
· IMDG	
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	III
· ADR, IMDG, IATA	
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]
· Marine pollutant:	Yes
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-D
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
None identified
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2022

Version number 3

Revision: 05.05.2022

Trade name: eTECTX Series Resists

(Contd. of page 10)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

· **Classification according to Regulation (EC) No 1272/2008**

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· **Department issuing SDS:** Product safety department

· **Contact:** Tom Cole, EHS Manager (tcole@kayakuAM.com)

· **Revision History:**

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4