

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **TempKoat™ P Series Resists**

· Article number: T111025, T111037, T111042, T111046, T111048

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment

· Product category PC30 Photo-chemicals

· Application of the substance / the mixture Photoresist

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535

Fax: +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511

Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

1-Methoxy-2-propanol acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

· Results of PBT and vPvB assessment

· PBT: Not applicable.



· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-65-6 EINECS: 203-603-9	1-Methoxy-2-propanol acetate	 Flam. Liq. 3, H226;  STOT SE 3, H336	50-75%
------------------------------------	------------------------------	---	--------

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 2)

Additional Components:		
	Proprietary Resin A	15-35%
	Proprietary Resin B	5-20%
CAS: 120-92-3 EINECS: 204-435-9	Cyclopentanone ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	<1.5%
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Ensure good ventilation/exhaust at the workplace.
 Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:**
 Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
- **Information about storage in one common storage facility:**
 Do not store together with oxidising and acidic materials.
 Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed containers.
 Protect from heat and direct sunlight.
 Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

 · **Ingredients with limit values that require monitoring at the workplace:**
108-65-6 1-Methoxy-2-propanol acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 4)

 · **Eye protection:**


Tightly sealed goggles

 · **Body protection:** Long-sleeved work clothes

SECTION 9: Physical and chemical properties

 · **9.1 Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:	Liquid
Colour:	Clear to light yellow
Odour:	Mild
Odour threshold:	Not determined.

 · **pH-value:** Not determined.

 · **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	146.4 °C

 · **Flash point:** 46 °C

 · **Flammability** Not applicable.

 · **Decomposition temperature:** Not determined.

 · **Ignition temperature:** Product is not selfigniting.

 · **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

 · **Explosion limits:**

Lower:	1.5 Vol %
Upper:	10.8 Vol %

 · **Vapour pressure at 20 °C:** 5 hPa

 · **Density:** See Other information

 · **Relative density** Not determined.

 · **Vapour density** Not determined.

 · **Evaporation rate** Not determined.

 · **Solubility in / Miscibility with water:**

Insoluble.

 · **Partition coefficient: n-octanol/water:** Not determined.

 · **Viscosity:**
Dynamic: Not determined.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 5)

Kinematic:	Not determined.				
· 9.2 Other information	Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)
	P1	Y111025	1.016	70-75	765
	P5	Y111037	1.042	60-65	655
	P10	Y111042	1.057	55-60	615
	P15	Y111046	1.065	50-55	570
	P20	Y111048	1.070	50-55	560

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons
Nitrogen oxides (NOx)
Amines

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

108-65-6 1-Methoxy-2-propanol acetate

Oral	LD50	8,532 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
Inhalative	LC50/6 h	4,345 ppm (Rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Experience with humans:** Target Organs: Central nervous system, kidney, liver, lungs
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 6)

 · **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information



- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|--|--|
| · 14.1 UN-Number
· ADR, IMDG, IATA | UN1866 |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | RESIN SOLUTION |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA

<div style="text-align: center;">  </div> | <div style="text-align: center;">  </div> |
| · Class
· Label | 3 Flammable liquids.
3 |
| · 14.4 Packing group
· ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 7)

· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

- Regulated explosives precursors

None of the ingredients is listed.

- Regulated poisons

None of the ingredients is listed.

- Reportable explosives precursors

None of the ingredients is listed.

- Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 20.05.2025

Version number 5

Revision: 20.05.2025

Trade name: TempKoat™ P Series Resists

(Contd. of page 8)

· Relevant phrases*H226 Flammable liquid and vapour.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.***· Department issuing SDS: Product safety department****· Contact:** Tom Cole, EHS Manager (tcole@kayakuam.com)**· Abbreviations and acronyms:***ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 3: Flammable liquids – Category 3**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

GB