

Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UniLOR® N Series Resists
- · Article number: T211132, T211128, T211122
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535

Fax: +44-0-1788-535835 Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Repr. 1A H360-H362 May damage fertility or the unborn child. May cause harm to breast-fed children.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 1)



Eye Dam. 1 H318 Causes serious eye damage.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02 GHS05 GHS07 G

- · Signal word Danger
- · Hazard-determining components of labelling:

Proprietary Copolymer

1-Methoxy-2-propanol acetate

· Hazard statements

H226 Flammable liquid and vapour.H318 Causes serious eye damage.

H360-H362 May damage fertility or the unborn child. May cause harm to breast-fed children.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P263 Avoid contact during pregnancy and while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

4.4 % of the mixture consists of component(s) of unknown toxicity.

(Contd. on page 3)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 2)

Contains 4.4 % of components with unknown hazards to the aquatic environment. Restricted to professional users.

· 2.3 Other hazards

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 108-65-6	1-Methoxy-2-propanol acetate	60-80%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🕔 STOT SE 3, H336	
	Proprietary Copolymer	10-25%
	😵 Repr. 1A, H360-H362; STOT RE 2, H373; <page-header> Eye Dam. 1, H318</page-header>	
	Amido ether	1-5%
	♦ Acute Tox. 4, H302; Eye Irrit. 2, H319	
CAS: 120-92-3	Cyclopentanone	1-5%
EINECS: 204-435-9	🚸 Flam. Liq. 3, H226; 🕠 Skin Irrit. 2, H315; Eye Irrit. 2, H319	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 3)

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 4)

Ingredients with limit values that require monitoring at the workplace:

108-65-6 1-Methoxy-2-propanol acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Red-brown
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 146.4 °C

• Flash point: $46 \, ^{\circ}C$

· Flammability (solid, gas): Not applicable.

• **Decomposition temperature:** Not determined.

(Contd. on page 6)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

					(Contd	. of page .
Ignition temperature:	Product	is not selfign	iting.			
Explosive properties:	Product is not explosive. However, formation of explosive air/v mixtures are possible.		r/vapou			
· Explosion limits:						
Lower:	1.5 Vol 9	%				
Upper:	10.8 Vol	%				
· Vapour pressure at 20 °C:	5 hPa					
Density:	See Other information					
· Vapour density	Not determined.					
· Evaporation rate	Not determined.					
· Solubility in / Miscibility with						
water:	Insolubl	e.				
Partition coefficient: n-octanol/water:	Not dete	rmined.				
· Viscosity:						
Dynamic:	Not determined.					
Kinematic:	Not dete	rmined.				
9.2 Other information	Name	Number	Sp. Grav.	. Vol.(%by wi	t.) VOC(g/L)	
·	N1.5	T211122	1.01	78	785	
	N2.5	T211128	1.02	71	730	
	N3.5	T211132	1.03	67	695	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Amines

Toxic gases / vapors

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	evant for classification:
120-92-3	Cyclopenta	none
Oral	LD50	1,820 mg/kg (Rat)

(Contd. on page 7)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

		(Contd. of page 6)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)
108-65-6 1	-Methoxy-	-2-propanol acetate
		8,532 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
Inhalative	LC50/6 h	4,345 ppm (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

May damage fertility or the unborn child. May cause harm to breast-fed children.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 7)

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	30 F-E,S-E
EMS Number: Stowage Category	7- <i>L</i> , <u>5-<i>L</i></u> A
14.7 Transport in bulk according to Annex II o	of .
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml



Printing date 03.04.2024 Version number 2 Revision: 03.04.2024

Trade name: UniLOR® N Series Resists

(Contd. of page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2