

# Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 29.08.2022

#### Printing date 29.08.2022 Version number 1 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: TempKoat<sup>TM</sup> N Series Resists · Article number: T212045 1.2 Relevant identified uses of the substance or mixture and uses advised against • Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment • Product category PC30 Photo-chemicals · Application of the substance / the mixture Photoresist · 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials 200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818 Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Vallev Rugby, Warwickshire CV21 1TW, UK *Tel:* +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com • Further information obtainable from: Product Safety Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency: 703-527-3887 (24 hr)

# **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB



Revision: 29.08.2022

Printing date 29.08.2022

Version number 1

Trade name:  $TempKoat^{TM} N$  Series Resists

	<b>g to Regulation (EC) No 1272/2008</b> sified and labelled according to the GB CLP regulation.
	sified and labelled according to the GB CLP regulation.
	sified and labelled according to the GB CLP regulation.
Hazard pictograms	
<u> { 🖞 / { ! / </u>	
GHS02 GHS07	
Signal word Warnir	ng
Hazard-determining	g components of labelling:
1-Methoxy-2-propar	
Hazard statements	
H226 Flammable lie	quid and vapour.
	owsiness or dizziness.
Precautionary state	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wear protective gloves/protective clothing/eye protection/face protection.
	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	IF ON SKIN: Wash with plenty of soap and water.
	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position
	comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i
	present and easy to do. Continue rinsing.
	If skin irritation occurs: Get medical advice/attention.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information	
8.1 % of the mixture	e consists of component(s) of unknown toxicity.
	components with unknown hazards to the aquatic environment.
2.3 Other hazards	1
Results of PBT and	l vPvB assessment
<b>PBT:</b> Not applicable	
vPvB: Not applicable	

# SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB —



Printing date 29.08.2022

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

		(Contd. of page 2)
· Dangerous compone	ents:	
CAS: 108-65-6	1-Methoxy-2-propanol acetate	25-50%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🕔 STOT SE 3, H336	
	Amido ether	5-15%
CAS: 120-92-3	Cyclopentanone	1-5%
EINECS: 204-435-9	🚸 Flam. Liq. 3, H226; 🐠 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
· Additional Compone	ents:	
Proprietary Copolyn	ner -	25-50%
A 1 1 1 . C		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

## **SECTION 6:** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.
6.2 Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

(Contd. on page 4)

GB –

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

(Contd. of page 3)

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# SECTION 7: Handling and storage

• 7.1 Precautions for safe handling

- *Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.*
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Do not store together with oxidising and acidic materials.
- Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

## 108-65-6 1-Methoxy-2-propanol acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm

Long-term value: 274 mg/m<sup>3</sup>, 50 ppm

Sk

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.* • *Material of gloves Nitrile rubber, NBR* 

(Contd. on page 5)



Printing date 29.08.2022

<sup>· 8.1</sup> Control parameters

GB —



Printing date 29.08.2022

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

(Contd. of page 4)

 $\cdot$  Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

9.1 Information on basic physical and of	chemical properties
General Information Appearance:	
Form:	Liquid
Colour:	Light yellow
Odour:	Sweetish
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: 146.4 °C
Flash point:	46 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
Vapour pressure at 20 °C:	5 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
	Not determined. Not determined.

GB -



Printing date 29.08.2022

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

					(Contd. of pag
• Solvent content: Organic solvents:	25-	50 %			
•9.2 Other information	Table 1. Product sp	ecific gravity an	d VOC data.		
	Name	Product No.	Sp. Grav.	Vol.(%by wt.)	VOC (g/L)
	TempKoat™ N15	T212045	1.07	50-55	540

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid
- Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide Hydrocarbons Nitrogen oxides (NOx) Sulphur oxides (SOx)

## SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

## · LD/LC50 values relevant for classification:

108-65-6 1-Methoxy-2-propanol acetate				
Oral	LD50	8,532 mg/kg (Rat)		
Dermal	LD50	8,532 mg/kg (Rat) >5,000 mg/kg (Rat) 4,345 ppm (Rat)		
Inhalative	LC50/6 h	4,345 ppm (Rat)		

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 29.08.2022

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 29.08.2022

(Contd. of page 6)

Trade name: TempKoat<sup>TM</sup> N Series Resists

· Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
· Class · Label	3 Flammable liquids. 3	
· Label	-	
	-	



Printing date 29.08.2022

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

	(Contd. of page
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
14.7 Transport in bulk according to Annex II of	f
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)



Printing date 29.08.2022

Version number 1

Revision: 29.08.2022

Trade name: TempKoat<sup>TM</sup> N Series Resists

(Contd. of page 8) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 GB