

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

1 Identification

- **Product identifier**
- **Trade name:** TempKoat™ N Series Resists
- **Product number:** T212045
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Information department:**
 Product Safety
 Email: productsafety@kayakuAM.com
- **Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
 1-Methoxy-2-propanol acetate
- **Hazard statements**
 H226 Flammable liquid and vapor.
 H336 May cause drowsiness or dizziness.
- **Precautionary statements**
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P302+P352 If on skin: Wash with plenty of soap and water.
 P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

8.1 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

108-65-6	1-Methoxy-2-propanol acetate ⚠ Flammable Liquids 3, H226; ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	25-50%
	Amido ether ⚠ Acute Toxicity - Oral 4, H302; Eye Irritation 2B, H320	5-15%
120-92-3	Cyclopentanone ⚠ Flammable Liquids 3, H226; ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	1-5%

· **Additional Components:**

Proprietary Copolymer	25-50%
-----------------------	--------

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.
- **After swallowing:**
Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
108-65-6	1-Methoxy-2-propanol acetate	50 ppm
120-92-3	Cyclopentanone	0.87 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 3)

· PAC-2:		
108-65-6	1-Methoxy-2-propanol acetate	1,000 ppm
120-92-3	Cyclopentanone	9.5 ppm
· PAC-3:		
108-65-6	1-Methoxy-2-propanol acetate	5000* ppm
120-92-3	Cyclopentanone	57 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaust at the workplace.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**
 Do not store together with oxidizing and acidic materials.
 Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
 Keep container well-sealed in cool, dry location.
 Protect from heat and direct sunlight.
 Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

108-65-6 1-Methoxy-2-propanol acetate	
WEEL	Long-term value: 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory equipment:**
 In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 4)

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material** Contact glove manufacture for break-through time.

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Liquid
Color:	Light yellow
Odor:	Sweet
Odor threshold:	Not determined.

 · **pH-value:** Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	146.4 °C (295.5 °F)

 · **Flash point:** 46 °C (114.8 °F)

 · **Flammability (solid, gaseous):** Not applicable.

 · **Decomposition temperature:** Not determined.

 · **Auto igniting:** Product is not selfigniting.

 · **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.5 Vol %
Upper:	10.8 Vol %

 · **Vapor pressure at 20 °C (68 °F):** 5 hPa (3.8 mm Hg)

 · **Density:** See other information

 · **Relative density** Not determined.

 · **Vapor density** Not determined.

 · **Evaporation rate** 1.6-2.3 (BuAc=1)

· Solubility in / Miscibility with
Water: Fully miscible.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 5)

 · **Partition coefficient (n-octanol/water):** Not determined.

 · **Viscosity:**

 Dynamic: Not determined.

 Kinematic: Not determined.

 · **Solvent content:**

 Organic solvents: 25-50 %

 VOC content: 25-50 %

 · **Other information** Table 1. Product specific gravity and VOC data.

Name	Product No.	Sp. Grav.	Vol. (% by wt.)	VOC (g/L)
TempKoat™ N15	T212045	1.07	50-55	540

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
 - Contact with incompatible materials.
 - Heat, flames and sparks. Extremes of temperature and direct sunlight.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Hydrocarbons
 - Nitrogen oxides (NO_x)
 - Sulfur oxides (SO_x)

11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**
108-65-6 1-Methoxy-2-propanol acetate

Oral	LD50	8,532 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
Inhalative	LC50/6 h	4,345 ppm (Rat)

 · **Primary irritant effect:**

 · **on the skin:** No irritant effect.

 · **on the eye:** No irritating effect.

 · **Sensitization:** No sensitizing effects known.

 · **Experience with humans:** Target Organs: Central nervous system, kidney, liver, lungs

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 6)

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

· **NTP (National Toxicology Program)**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

Disposal must be made in accordance with Federal, State, and Local regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1866

· **UN proper shipping name**

· **DOT**

Resin solution

· **ADR, IMDG, IATA**

RESIN SOLUTION

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 7)

 · **Transport hazard class(es)**

 · **DOT**

 · **Class**

3 Flammable liquids

 · **Label**

3

 · **ADR, IMDG, IATA**

 · **Class**

3 Flammable liquids

 · **Label**

3

 · **Packing group**

 · **DOT, ADR, IMDG, IATA**

III

 · **Environmental hazards:**

Not applicable.

 · **Special precautions for user**

Warning: Flammable liquids

 · **Hazard identification number (Kemler code):**

30

 · **EMS Number:**

F-E, S-E

 · **Stowage Category**

A

 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

 · **Transport/Additional information:**

 · **DOT**

 · **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

 · **ADR**

 · **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

 · **IMDG**

 · **Limited quantities (LQ)**

5L

 · **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

 · **UN "Model Regulation":**

UN 1866 RESIN SOLUTION, 3, III

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 8)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

This product contains at least one component that is not listed (and is not excluded from listing) on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory, and therefore can be used only for research and development purposes under the conditions described in the Code of Federal Regulations at 40 CFR 720.36.

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value)**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Massachusetts State Right To Know List**

120-92-3 Cyclopentanone

· **New Jersey State Right To Know List**

120-92-3 Cyclopentanone

· **Pennsylvania Hazardous Substances List**

120-92-3 Cyclopentanone

· **California SCAQMD Rule 443.1 VOC's:** No information available.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 9)

Hazard pictograms


GHS02 GHS07

Signal word Warning

Hazard-determining components of labeling:

1-Methoxy-2-propanol acetate

Hazard statements

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Product safety department

Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

Revision History: New SDS

Date of preparation / last revision 08/29/2022

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/29/2022

Reviewed on 08/29/2022

Trade name: TempKoat™ N Series Resists

(Contd. of page 10)

*LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flammable Liquids 3: Flammable liquids – Category 3**Acute Toxicity - Oral 4: Acute toxicity – Category 4**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*

US