GB



Safety data sheet according to UK REACH

Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: TempKoatTM N Series Resists

• Article number: T212045

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment

• **Product category** PC30 Photo-chemicals

· Application of the substance / the mixture Photoresist

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials
200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Valley Rugby, Warwickshire CV21 1TW, UK Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com

• Further information obtainable from:

Product Safety Email: productsafety@kayakuam.com • 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008
 GHS02 flame
 Flam. Liq. 3 H226 Flammable liquid and vapour.
 GHS07
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. (Contd. on page 2)



Revision: 29.01.2025

Printing date 29.01.2025

Version number 5

Trade name: TempKoatTM N Series Resists

	(Contd. of page 1)
· 2.2 Labe	l elements
	g according to Regulation (EC) No 1272/2008
	luct is classified and labelled according to the GB CLP regulation.
· Hazard J	pictograms
	\wedge
Nr.	
GHS02	GHS07
011502	011507
· Signal w	ord Warning
Hazard-	determining components of labelling:
	xy-2-propanol acetate
	ary Copolymer
-	statements
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
Н335-Н.	336 May cause respiratory irritation. May cause drowsiness or dizziness.
	onary statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P263	Avoid contact during pregnancy and while nursing.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P	
P302+P	
P304+P	
	comfortable for breathing.
P305+P.	351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P333+P	
<i>P337+P</i>	
P370+P	
D 40 2 - D	dioxide.
P403+P	1 1
P501	Dispose of contents/container in accordance with local/regional/national/international
1 .] .]:4:	regulations.
	al information:
	<i>the mixture consists of component(s) of unknown toxicity.</i> 8.1 % of components with unknown hazards to the aquatic environment.
	r hazards
	<i>r nazaras</i> the ingredients are included in the list established in accordance with Article 59(1) for having endocrine
	g properties.
	the ingredients are substances identified as having endocrine disrupting properties in accordance with
	ria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU)
2018/603	

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 3)

⁻ GB -



Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 108-65-6	1-Methoxy-2-propanol acetate	25-50%		
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336			
	Proprietary Copolymer	25-50%		
	𝚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335			
	Proprietary crosslinker	5-15%		
CAS: 120-92-3	Cyclopentanone	1-5%		
	🚸 Flam. Liq. 3, H226; 솻 Skin Irrit. 2, H315; Eye Irrit. 2, H319			
• Additional informat	ion: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- *After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents:
- Alcohol resistant foam

Fire-extinguishing powder

- Carbon dioxide
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.

(Contd. on page 4)

GB -



Revision: 29.01.2025

Printing date 29.01.2025

Version number 5

Trade name: TempKoatTM N Series Resists

(Contd. of page 3)

• 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

• *Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and containers: No special requirements.

• Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

• Further information about storage conditions:

Store frozen.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 1-Methoxy-2-propanol acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

(Contd. of page 4)

· Protection of hands:



- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

General Information Appearance:		
11	Liquid	
Colour:	Liquid Light yellow	
Odour:	Sweetish	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	146.4 °C	
Flash point:	46 °C	
Flammability	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.	
Explosion limits:		
Lower:	1.5 Vol %	
Upper:	10.8 Vol %	
Vapour pressure at 20 °C:	5 hPa	
Density:	See Other information	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	



Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

	(Contd. of J	page 5)
• Solubility in / Miscibility with water:	Insoluble.	
• Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
• 9.2 Other information	Name Number Sp. Grav. VOC(%by wt.) VOC(g/L) N15 T212045 1.07 50-55 540	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

· 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Hydrocarbons Nitrogen oxides (NOx) Sulphur oxides (SOx)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· LD/LC50 values relevant for classification:

108-65-6 1-Methoxy-2-propanol acetate					
Oral	LD50	8,532 mg/kg (Rat)			
	LD50	8,532 mg/kg (Rat) >5,000 mg/kg (Rat)			
Inhalative	LC50/6 h	4,345 ppm (Rat)			

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

• Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

[·] Acute toxicity Based on available data, the classification criteria are not met.

GB -



Printing date 29.01.2025

Safety data sheet according to UK REACH

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

(Contd. of page 6)

· STOT-single exposure

- May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information • 14.1 UN-Number UN1866 • ADR, IMDG, IATA UN1866 • 14.2 UN proper shipping name RESIN SOLUTION • ADR, IMDG, IATA RESIN SOLUTION • 14.3 Transport hazard class(es) ADR, IMDG, IATA • ADR, IMDG, IATA Solution • Class 3 Flammable liquids. • Label 3



Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

	(Contd. of page	
14.4 Packing group		
ADR, IMDĞ, IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	F- E , S - E	
Stowage Category	A	
14.7 Transport in bulk according to Annex II of	of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)

GB



Printing date 29.01.2025

Version number 5

Revision: 29.01.2025

Trade name: TempKoatTM N Series Resists

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com) · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3