Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Version number 4

Revision: 31.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Functional electronic epoxy curing agent
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from: Product Safety
Email: productsafety@kayakuAM.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS	05 corrosion
Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
<i>Skin Sens. 1</i>	07 H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Aquatic Chronic	c 3 H412 Harmful to aquatic life with long lasting effects.
	rding to Regulation (EC) No 1272/2008 classified and labelled according to the CLP regulation. ams
Signal word Da	

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 1) · Hazard-determining components of labelling: Fatty acids, tall-oil, reaction products with tetraethylenepentamine *Tetraethylenepentamine* · Hazard statements H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapours/spray. P261 P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of water. *P304+P341* IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	75-100%
EINECS: 203-986-2	Tetraethylenepentamine Skin Corr. IB, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	5-15%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



[•] After inhalation:

EU —

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 2)

• After eye contact: Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• *After swallowing:* Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Ensure adequate ventilation.

• 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

• *Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and containers: No special requirements.

(Contd. on page 4)

EU



according to 1907/2006/EC, Article 31

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 3)

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials. • Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from food and beverages. *Immediately remove all soiled and contaminated clothing* Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)



Printing date 31.03.2020

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Υ/ΛΚ

ADVANCED MATERIALS

Version number 4

Revision: 31.03.2020

(Contd. of page 4)

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

SECTION 9: Physical and chemic	cal properties
• 9.1 Information on basic physical and ch	nemical properties
• General Information • Appearance:	
Form:	Liquid
Colour:	Amber coloured
· Odour:	Characteristic
• Odour threshold:	Not determined.
· pH-value:	Alkaline
• Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	195 °C
· Flammability (solid, gas):	Not applicable.
• Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product does not present an explosion hazard.
• Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

EU —

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 5)

· 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. *Contact with incompatible materials.*

· 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Ammonia

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

112-57-2 Tetraethylenepentamine

Dermal LD50 660 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes severe skin burns and eye damage.
- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

(Contd. on page 7)





DVANCED MATERIALS

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

ADVANCED MATERIALS

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 6)

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information

· 14.1 UN-Number		
· ADR, ADN, IMDG, IATA	Not Regulated	
· 14.2 UN proper shipping name		
·ADR	Void	
· ADN, IMDG, IATA	Not Regulated	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Not Regulated	
· 14.4 Packing group		
· ADR, IMDG, IATA	Not Regulated	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Ann	nex II of	
Marpol and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Other regulations, limitations and prohibitive regulations

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

(Contd. on page 8)

EU -

according to 1907/2006/EC, Article 31

Printing date 31.03.2020

Version number 4

Revision: 31.03.2020

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

• Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

