

Printing date 03/30/2020

Reviewed on 03/30/2020

## 1 Identification

- **Product identifier**
- **Trade name:** *UV-3010 UV Curable Coating/Encapsulant*
- **Application of the substance / the mixture** *Encapsulant*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Kayaku Advanced Materials, Inc.  
 200 Flanders Road  
 Westborough, MA 01581  
 Tel: (617) 965-5511  
 Fax: (617) 965-5818
- **Information department:**  
 Product Safety  
 Email: [productsafety@kayakuAM.com](mailto:productsafety@kayakuAM.com)
- **Emergency telephone number:**  
 Kayaku Advanced Materials : 617-965-5511  
 Chemtrec USA Emergency : 800-424-9300  
 Chemtrec International Emergency : 703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2                      H351 Suspected of causing cancer.



GHS09 Environment

Aquatic Acute 1      H400 Very toxic to aquatic life.

Aquatic Chronic 1   H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2                      H315 Causes skin irritation.

Eye Irrit. 2A                      H319 Causes serious eye irritation.

Skin Sens. 1                      H317 May cause an allergic skin reaction.

STOT SE 3                      H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08



GHS09

(Contd. on page 2)

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 1)

 · **Signal word** *Warning*

 · **Hazard-determining components of labeling:**
*Urethane acrylate oligomer*
*Isobornyl acrylate*
*Benzophenone*
*Trimethylolpropane ethoxylate triacrylate*

 · **Hazard statements**
*H315 Causes skin irritation.*
*H319 Causes serious eye irritation.*
*H317 May cause an allergic skin reaction.*
*H351 Suspected of causing cancer.*
*H335 May cause respiratory irritation.*
*H400 Very toxic to aquatic life.*
*H410 Very toxic to aquatic life with long lasting effects.*

 · **Precautionary statements**
*P261 Avoid breathing dust/fume/gas/mist/vapors/spray*
*P273 Avoid release to the environment.*
*P280 Wear protective gloves/protective clothing/eye protection/face protection.*
*P301+P310 If swallowed: Immediately call a poison center/doctor.*
*P302+P352 If on skin: Wash with plenty of soap and water.*
*P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.*
*P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
*P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*
*P337+P313 If eye irritation persists: Get medical advice/attention.*
*P403+P233 Store in a well-ventilated place. Keep container tightly closed.*
*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

 · **Classification system:**

 · **NFPA ratings (scale 0 - 4)**

*Health = 2*
*Fire = 1*
*Reactivity = 0*

 · **HMIS-ratings (scale 0 - 4)**

*Health = 2*
*Fire = 1*
*Reactivity = 0*

 · **Other hazards**

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

### 3 Composition/information on ingredients

 · **Chemical characterization: Mixtures**

 · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 2)

**Dangerous components:**

	Urethane acrylate oligomer	40-60%
	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	
5888-33-5	Isobornyl acrylate	25-50%
	⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
	Aromatic Urethane Acrylate	10-25%
	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
28961-43-5	Trimethylolpropane ethoxylate triacrylate	5-15%
	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
	Proprietary Resin	5-15%
	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227	
	Proprietary photoinitiator	1-5%
	⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411	
119-61-9	Benzophenone	1-5%
	⚠ Carc. 2, H351; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

### 4 First-aid measures

**Description of first aid measures**
**General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

**After swallowing:** Do not induce vomiting; immediately call a doctor.

**Information for doctor:**

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### 5 Fire-fighting measures

**Extinguishing media**
**Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
 Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation  
 Keep away from ignition sources
- **Environmental precautions:**  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

119-61-9	Benzophenone	1.5 mg/m <sup>3</sup>
----------	--------------	-----------------------

### · PAC-2:

119-61-9	Benzophenone	90 mg/m <sup>3</sup>
----------	--------------	----------------------

### · PAC-3:

119-61-9	Benzophenone	310 mg/m <sup>3</sup>
----------	--------------	-----------------------

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaust at the workplace.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**  
 Do not store together with alkalis (caustic solutions).  
 Do not store together with oxidizing and acidic materials.
- **Further information about storage conditions:**  
 Keep container well-sealed in cool, dry location.  
 Protect from heat and direct sunlight.  
 Store receptacle in a well ventilated area.

(Contd. on page 5)

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

 · **Specific end use(s)** No further relevant information available.

(Contd. of page 4)

## 8 Exposure controls/personal protection

 · **Additional information about design of technical systems:** No further data; see item 7.

 · **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 119-61-9 Benzophenone

WEEL	Long-term value: 0.5 mg/m <sup>3</sup>
------	--

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

 · **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material** Contact glove manufacture for break-through time.

 · **Eye protection:**


Tightly sealed goggles

## 9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

<b>Form:</b>	Liquid
--------------	--------

<b>Color:</b>	Clear
---------------	-------

<b>Odor:</b>	Sweet
--------------	-------

<b>Odor threshold:</b>	Not determined.
------------------------	-----------------

<b>pH-value:</b>	Not determined.
------------------	-----------------

(Contd. on page 6)

## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 5)

· <b>Change in condition</b>	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· <b>Flash point:</b>	93 °C (199.4 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Not determined.
· <b>Explosion limits:</b>	
Lower:	Not determined.
Upper:	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density:</b>	See other information
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
Water:	Water miscible No
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	0.0 %
Solids content:	100 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
Heat, flames and sparks. Extremes of temperature and direct sunlight.  
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

US

(Contd. on page 7)

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 6)

## 11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**
**5888-33-5 Isobornyl acrylate**

Oral LD50 4890 mg/kg (Rat)

Dermal LD50 &gt;5000 mg/kg (rabbit)

 · **Primary irritant effect:**

 · **on the skin:** Irritant to skin and mucous membranes.

 · **on the eye:** Irritating effect.

 · **Sensitization:** Sensitization possible through skin contact.

 · **Additional toxicological information:**

 The product shows the following dangers according to internally approved calculation methods for preparations:  
 Harmful

Irritant

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

119-61-9 Benzophenone

2B

 · **NTP (National Toxicology Program)**

None of the ingredients are listed.

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

## 12 Ecological information

 · **Toxicity**

 · **Aquatic toxicity:**
**5888-33-5 Isobornyl acrylate**

EC50/48 h 1.1 mg/l (daphnia magna)

**Proprietary photoinitiator**

EC50/48 h 26 mg/l (daphnia magna)

 · **Persistence and degradability** No further relevant information available.

 · **Behavior in environmental systems:**

 · **Bioaccumulative potential** No further relevant information available.

 · **Mobility in soil** No further relevant information available.

 · **Ecotoxicological effects:**

 · **Remark:** Very toxic for fish

 · **Additional ecological information:**

 · **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

(Contd. on page 8)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**


(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.  
Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

### 14 Transport information

· <b>UN-Number</b>	UN3082
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s. (Isobornyl acrylate, Benzophenone)
· <b>DOT, ADR</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate, Benzophenone), MARINE POLLUTANT
· <b>IMDG</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate, Benzophenone)
· <b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate, Benzophenone)
· <b>Transport hazard class(es)</b>	
· <b>DOT, ADR, IMDG, IATA</b>	
	
· <b>Class</b>	9 Miscellaneous dangerous substances and articles
· <b>Label</b>	9
· <b>Packing group</b>	III
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: Isobornyl acrylate
· <b>Marine pollutant:</b>	Yes (DOT)
· <b>Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles
· <b>Hazard identification number (Kemler code):</b>	90
· <b>EMS Number:</b>	F-A,S-F
· <b>Stowage Category</b>	A

(Contd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 8)

· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: No limit On cargo aircraft only: No limit
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (ISOBORNYL ACRYLATE, BENZOPHENONE), 9, III

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

#### · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

#### · Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

#### · Proposition 65

#### · Chemicals known to cause cancer:

119-61-9 Benzophenone

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

#### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients are listed.

#### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**

(Contd. of page 9)

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

**· New Jersey State Right To Know List**

119-61-9 Benzophenone

**· Pennsylvania Hazardous Substances List**

119-61-9 Benzophenone

**· California SCAQMD Rule 443.1 VOC's:** No information available.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**


GHS07    GHS08    GHS09

**· Signal word** Warning

**· Hazard-determining components of labeling:**

Urethane acrylate oligomer

Isobornyl acrylate

Benzophenone

Trimethylolpropane ethoxylate triacrylate

**· Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**· Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· National regulations:**
**· Other regulations, limitations and prohibitive regulations**

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

(Contd. on page 11)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/30/2020

Reviewed on 03/30/2020

**Trade name: UV-3010 UV Curable Coating/Encapsulant**· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 10)

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Product safety department· **Contact:** Tom Cole, EHS Manager (tcole@kayakuAM.com)· **Revision History:** The manufacturer's information in Section 1 has been updated.· **Date of preparation / last revision** 03/30/2020 / 1· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2