

Printing date 08/12/2019 Reviewed on 08/12/2019

### 1 Identification

- · Product identifier
- · Trade name: 100 PMMA Series Resists in Anisole
- · Product number:

M630001, M630002, M630003, M630004, M630504, M630005, M630506, M630007, M630508, M630009, M630010

- · Application of the substance / the mixture Photoresist
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

**Product Safety** 

Email: productsafety@kayakuAM.com

· Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labeling: Anisole

(Contd. on page 2)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 1)

#### · Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor. P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- $\cdot$  **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
100-66-3 Anisole	80-100%
Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	

(Contd. on page 3)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 2)

· Additional Components:

9010-88-2 Poly(methyl methacrylate-co-ethyl acrylate)

1-20%

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Use only under yellow light

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Keep container well-sealed in cool, dry location.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

- · Respiratory equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 4)

· Material of gloves

VITON®

Nitrile rubber, NBR

- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity: Dynamic:

Information on basic physical and General Information	
Appearance:	
Form:	Liquid
Color:	Clear to light yellow
Odor:	Strong
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	184 °C (363.2 °F)
Flash point:	43 °C (109.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	475 °C (887 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	0.4 hPa (0.3 mm Hg)
Density:	Not determined.
Relative density	See Table 1 Other Information
Vapor density	Not determined.
Evaporation rate	Not determined.

Not determined.

(Contd. on page 6)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

	(Contd. of pag
Kinematic:	Not determined.
· Solvent content:	
VOC content:	See Table 1 below
· Other information	Table 1. Product specific gravity and VOC data.
	Name Number Sp. Grav. Vol.(%by wt.) VOC (g/L)
	100A1 M630001 0.996 99 985
	100A2 M630002 0.997 98 980
	100A3 M630003 0.999 97 970
	100A4 M630004 1.001 96 960
	100A4.5 M630504 1.002 95.5 955
	100A5 M630005 1.003 95 950
	100A6 M630506 1.005 94 945
	100A7 M630007 1.007 93 935
	100A8 M630508 1.009 92 930
	100A9 M630009 1.011 91 920
	100A10 M630010 1.022 90 920

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal use conditions
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Phenol

methyl methacrylate

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
100-66-3 Anisole				
Oral	LD50	3700 mg/kg (Rat)		
Dermal	LD50	>5000 mg/kg (rabbit)		

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

## 12 Ecological information

· Toxicity

· Aquatic toxicity:

#### 100-66-3 Anisole

EC50/24 h | 40 mg/l (daphnia magna)

EC50/96 hr 162 mg/l (green algae)

LC50/48 hr | 120 mg/L (Cyprinus carpio (common carp))

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

### 14 Transport information

· UN-Number

*· DOT · ADR, IMDG, IATA*NA1866

UN1866



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 7) · UN proper shipping name · DOT, IMDG, IATA RESIN SOLUTION  $\cdot ADR$ 1866 RESIN SOLUTION · Transport hazard class(es)  $\cdot DOT$ · Class 3 Flammable liquids · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards:

· Marine pollutant:

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): F-E,S-E· EMS Number:

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN ''Model Regulation'': UN1866, RESIN SOLUTION, 3, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

(Contd. on page 9)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 8)

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

#### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients are listed.

#### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

### · New Jersey State Right To Know List

100-66-3 Anisole

- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Anisole

#### · Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

*P301+P310* If swallowed: Immediately call a poison center/doctor.

*P302+P352 If on skin: Wash with plenty of soap and water.* 

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 10)



Printing date 08/12/2019 Reviewed on 08/12/2019

Trade name: 100 PMMA Series Resists in Anisole

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- · Date of preparation / last revision 08/12/2019 / 2
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$ 

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- IIS