

Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 50 PMMA Series Resists in Anisole
- · Article number:

M530001, M530002, M530003, M530004, M530005, M530506, M530007, M530508, M530009, M530010, M530511, M530012, M530030

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 1)

- · Signal word Warning
- · Hazard-determining components of labelling:

Anisole

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	· Dangerous components:							
Γ	CAS: 100-66-3		70-100%					
		Tlam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335						
Γ	CAS: 25086-15-1	Poly(methyl methacrylate-co-methacrylic acid)	1-30%					
		♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335						

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Keep receptacles tightly sealed.

Prevent formation of aerosols.

Use only in well ventilated areas.

Use only under yellow light

(Contd. on page 4)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

- · Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions:} \\$

Keep container tightly sealed.

Protect from exposure to the light.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)




Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 4)

· Eye protection:



SECTION 9: Physical and chemical properties
· 9.1 Information on basic physical and chemical properties
· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

· Odour:

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Undetermined. Melting point/freezing point: Initial boiling point and boiling range: 184 °C

43 °*C* · Flash point:

· Flammability (solid, gas): Not applicable.

475 °C · Ignition temperature:

· Decomposition temperature: Not determined.

Product is not selfigniting. · Auto-ignition temperature:

Product is not explosive. However, formation of explosive air/vapour · Explosive properties:

mixtures are possible.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapour pressure at 20 °C: 0.4 hPa

· Density: Not determined

· Relative density Not determined.

See Table 1 Other Information

· Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Not miscible or difficult to mix. water:

Not determined. · Partition coefficient: n-octanol/water:

· Viscosity:

Dynamic: Not determined.

(Contd. on page 6)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

				(Contd. of page
Kinematic:	Not determined.			
· 9.2 Other information	Name Number	Sp. Grav.	Vol.(%by wt.)	VOC(g/L)
, and the second	50A1 M530001	0.998	99	990
	50A2 M530002	0.999	98	980
	50A3 M530003	1.000	97	970
	50A4 M530004	1.001	96	960
	50A5 M530005	1.003	95	950
	50A6 M530506	1.005	94	945
	50A7 M530007	1.006	93	935
	50A8 M530508	1.009	92	930
	50A9 M530009	1.010	91	920
	50A10 M530010	1.013	90	910
	50A11 M530511	1.015	89	905
	50A12 M530012	1.016	88	895
	50A30 M530030	1.034	70	725

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal use conditions
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Phenol

methyl methacrylate

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:				
100-66-3		···		
Oral	LD50	3700 mg/kg (Rat)		
Dermal	LD50	>5000 mg/kg (rabbit)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 6)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:						
	100-66-3 An	isole				
	EC50/24 h	40 mg/l (daphnia magna)				
	EC50/96 hr	162 mg/l (green algae)				
	LC50/48 hr	120 mg/L (Cyprinus carpio (common carp))				

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Q TA	α		7 7 7	11.	40			C	-4:
שנס		ж	JΝ	14:	T rai	(น เก	form	(1150)1

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1866
- · 14.2 UN proper shipping name
- · ADR, IMDG, IATA RESIN SOLUTION

(Contd. on page 8)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

		(Contd. of page 7)	
· 14.3 Transport hazard class(es)			
· ADR, IMDG, IATA			
· Class	3 Flammable liquids.		
· Label	3		
· 14.4 Packing group			
· ADR, IMDG, IATA	III		
· 14.5 Environmental hazards:			
· Marine pollutant:	No		
· 14.6 Special precautions for user	Warning: Flammable liquids.		
· Danger code (Kemler):	30		
· EMS Number:	F- E , S - D		
· 14.7 Transport in bulk according to Annex II of			
Marpol and the IBC Code	Not applicable.		
· Transport/Additional information:			

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

5L

D/E

UN1866, RESIN SOLUTION, 3, III

3

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

· Limited quantities (LQ)

· Tunnel restriction code

· UN "Model Regulation":

· Transport category

H335 May cause respiratory irritation.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)

(Contd. on page 9)



Printing date 12.08.2019 Version number 3 Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Anisole

(Contd. of page 8)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- DII