

Printing date 22.08.2019

Version number 4

Revision: 22.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: LOR A Series Resists

· Article number:

G516602, G516603, G516604, G516605, G516606, G516607, G516608, G516658, G516609, G516610, G516611, G516612, G516614, G516616, G516619

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- Further information obtainable from: Product Safety
 Email: productsafety@kayakuAM.com
 1.4 Emergency telephone number:
- Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. Hazard pictograms



· Signal word Warning

(Contd. on page 2)

EU -



Printing date 22.08.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

	(Contd. of page 1)
· Hazard-determining components of labelling:	
Cyclopentanone	
· Hazard statements	
H226 Flammable liquid and vapour.	
H315 Causes skin irritation.	
H319 Causes serious eye irritation.	
· Precautionary statements	
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignitions smoking.	on sources. No
P260 Do not breathe dust/fume/gas/mist/vapours/spray.	
P280 Wear protective gloves/protective clothing/eye protection/face protection.	
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
<i>P302+P352 IF ON SKIN: Wash with plenty of soap and water.</i>	
<i>P304+P341</i> IF INHALED: If breathing is difficult, remove victim to fresh air and keep at r comfortable for breathing.	est in a position
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove co	ontact lenses, if
present and easy to do. Continue rinsing.	
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.	
<i>P337+P313</i> If eye irritation persists: Get medical advice/attention.	
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.	
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.	
P370+P378 In case of fire: Use for extinction: Carbon dioxide.	
P403+P235 Store in a well-ventilated place. Keep cool.	
P501 Dispose of contents/container in accordance with local/regional/national	al/international
regulations.	
· 2.3 Other hazards	

· Results of PBT and vPvB assessment

· *PBT:* Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 120-92-3	Cyclopentanone	65-90%
EINECS: 204-435-9 Index number: 606-025-00	9 Flam. Liq. 3, H226; (1) Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 107-98-2	1-methoxy-2-propanol	5-25%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
Index number: 603-064-00	-3	
CAS: 102322-80-5	Polyaliphatic imide copolymer	1-20%
	🚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
· Additional Components:		
Proprietary Dye A		<1%
• Additional information: F	or the wording of the listed hazard phrases refer to section 16.	

(Contd. on page 3)



Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam
- *Fire-extinguishing powder*
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents:
- Water with full jet
- Water
- · 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

⁻ EU



Printing date 22.08.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4

Revision: 22.08.2019

(Contd. of page 3)

Trade name: LOR A Series Resists

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No release to water in manufacturing, process, use or disposal. Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep receptacles tightly sealed.

Use only under yellow light

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidising and acidic materials.
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Skin

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

nume. Lon 11 Series Resists

EU -



Printing date 22.08.2019

Version number 4

Revision: 22.08.2019

(Contd. of page 4)

Trade name: LOR A Series Resists

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves Nitrile rubber, NBR*

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance: Form:	Liquid
Form: Colour:	Liquid Red
Odour:	Slightly sweet
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	2.3 Vol %
Upper:	Not determined.
Vapour pressure at 20 °C:	12 hPa
Density:	Not determined
Relative density	See Table 1 Other Information
Vapour density	Not determined.
Evaporation rate	Not determined.

EU・



Printing date 22.08.2019

Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

					(Contd. of pag
Solubility in / Miscibility with water:	Not miscil	ble or diffic	cult to mix.		
Partition coefficient: n-octanol/water:	Not detern	Not determined.			
Viscosity:					
Dynamic:	Not determ	nined.			
Kinematic:	Not determ	nined.			
9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by w	vt.) $VOC(g/L)$
	LOR 0.5A	G516602	0.965	<u>98</u>	945
	LOR 0.7A	G516603	0.968	97	940
	LOR 1A	G516604	0.973	96	940
	LOR 2A	G516605	0.977	95	935
	LOR 3A	G516606	0.98	94	920
	LOR 4A	G516607	0.982	93	915
	LOR 5A	G516608	0.984	92	905
	LOR 6A	G516658	0.986	92	905
	LOR 7A	G516609	0.988	91	900
	LOR 8A	G516610	0.988	90	895
	LOR 10A	G516611	0.99	89	885
	LOR 15A	G516612	0.99	87	860
	LOR 20A	G516614	0.99	86	850
	LOR 30A	G516616	0.99	84	830
	LOR 50A	G516619	0.995	81	820

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

120-92-3 Cyclopentanone			
Oral	LD50	1180 mg/kg (Rat)	
	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>19.5 mg/l (Rat)	

(Contd. on page 7)

EU -



Printing date 22.08.2019

Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

		(Co	ontd. of page 6)
107-98-21	-methoxy-	-2-propanol	
Oral	LD50	5660 mg/kg (Rat)	
Dermal	LD50	13000 mg/kg (rabbit)	
Inhalative	LC50/4 h	54.6 mg/l (Rat)	
102322-80	-5 Polyalip	phatic imide copolymer	
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)	
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)	
· Primary ir	ritant effec	ct:	

· Skin corrosion/irritation

Causes skin irritation.

• Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• *Experience with humans:* No further relevant information available.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

 \cdot **Reproductive toxicity** Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

120-92-3 Cyclopentanone

EC50/48 h 100 mg/l (daphnia magna)

EC50/72 h >100 mg/l (scenedesmus subspicatus)

LC50/96 h >100 mg/l (fish)

107-98-2 1-methoxy-2-propanol

EC50/96 hr 23300 mg/l (daphnia magna)

>1000 mg/l (green algae)

LC50/96 h 20800 mg/l (Pimephales promelas)

• 12.2 Persistence and degradability Moderately /partly biodegradable

• 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)



Printing date 22.08.2019

Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name		
ADR	1866 RESIN SOLUTION	
IMDG, IATA	RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDĞ, IATA	III	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
Danger code (Kemler):	33	
EMS Number:	<i>F-E,<u>S-E</u></i>	
14.7 Transport in bulk according to Anne	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)

EU -



Printing date 22.08.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4

Revision: 22.08.2019

Trade name: LOR A Series Resists

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Classification according to Regulation (EC) No 1272/2008 Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuAM) · Revision History: The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated. · Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3