

Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: LOR B Series Resists
- · Article number:

G316702, G316703, G316704, G316707, G316708, G316709, G316710, G316711, G316712, G316715, G316716, G316719

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Warning

(Contd. on page 2)



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

(Contd. of page 1)

· Hazard-determining components of labelling:

Cyclopentanone

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 120-92-3	Cyclopentanone	65-90%
EINECS: 204-435-9 Index number: 606-025-00-9	Tlam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 102322-80-5	Polyaliphatic imide copolymer	1-20%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 107-98-2	1-methoxy-2-propanol	10-25%
EINECS: 203-539-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
Index number: 603-064-00-3		
	Proprietary Dye B	0.1-2%
	🗘 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	

· Additional information: For the wording of the listed hazard phrases refer to section 16.



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · *After skin contact: Immediately wash with water and soap and rinse thoroughly.*
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Use only under yellow light

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in a cool location.

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and cl	nemical properties
· General Information	
· Appearance:	
Form:	Liquid
Colour:	Yellow-brown
· Odour:	Sweetish
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	120 °C
· Flash point:	30 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	270 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.3 Vol %
Upper:	Not determined.
· Vapour pressure at 20 °C:	12 hPa
· Density:	Not determined
· Relative density	See Table 1 Other Information
· Vapour density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 6)



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

Solubility in / Miscibility with water:	Not missik	le or diffici	ult to mix		(Contd. of page
			iii io mix.		
Partition coefficient: n-octanol/water:	Not detern	iined.			
Viscosity:					
Dynamic:	Not detern	iined.			
Kinematic:	Not detern	Not determined.			
9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by wt.	.) <i>VOC</i> (<i>g</i> / <i>L</i>)
	LOR 0.7B	G316702	0.965	98	940
	LOR 1B	G316703	0.967	96	930
	LOR 2B	G316704	0.973	95	930
	LOR 3B	G316707	0.980	93	920
	LOR 5B	G316708	0.982	92	910
	LOR 6B	G316709	0.984	91	900
	LOR 7B	G316710	0.988	91	900
	<i>LOR 10B</i>	G316711	0.990	89	880
	LOR 15B	G316712	0.992	88	870
	<i>LOR 20B</i>	G316715	1.002	86	860
	<i>LOR 30B</i>	G316716	1.004	85	850
	LOR 50B	G316719	1.007	82	830

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

$\cdot L$	D/LC50 v	alues rele	vant for classification:
12	20-92-3 C	Cyclopenta	none
0	ral	LD50	1180 mg/kg (Rat)
D	ermal	LD50	>2000 mg/kg (rabbit)
In	halative	LC50/4 h	>19.5 mg/l (Rat)
10	07-98-2 1	-methoxy-	2-propanol
0	ral	LD50	5660 mg/kg (Rat)
D	ermal	LD50	13000 mg/kg (rabbit)

(Contd. on page 7)



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

		(Contd. of page 6)
Inhalative	LC50/4 h	54.6 mg/l (Rat)
102322-80	-5 Polyali _l	phatic imide copolymer
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxi	· Aquatic toxicity:	
120-92-3 Cy	clopentanone	
EC50/48 h	100 mg/l (daphnia magna)	
EC50/72 h	>100 mg/l (scenedesmus subspicatus)	
LC50/96 h	>100 mg/l (fish)	
107-98-2 1-1	methoxy-2-propanol	
	23300 mg/l (daphnia magna)	
	>1000 mg/l (green algae)	
LC50/96 h	20800 mg/l (Pimephales promelas)	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

(Contd. of page 7)

Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name ADR IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids. 33 F-E,S-E	
14.7 Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ) Transport category Tunnel restriction code	5L 3 D/E	
UN ''Model Regulation'':	UN1866, RESIN SOLUTION, 3, III	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 22.08.2019 Version number 3 Revision: 22.08.2019

Trade name: LOR B Series Resists

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3