Reviewed on 08/22/2019



Safety Data Sheet acc. to OSHA HCS

Printing date 08/22/2019

1 Identification

- · Product identifier
- · Trade name: LOR B Series Resists
- Product number: G316702, G316703, G316704, G316707, G316708, G316709, G316710, G316711, G316712, G316715, G316716, G316719
- · Application of the substance / the mixture Photoresist
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number:
- Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

• Hazard-determining components of labeling: Cyclopentanone

• Hazard statements H226 Flammable liquid and vapor. H315 Causes skin irritation.

(Contd. on page 2)

US



Trade name: LOR B Series Resists

Reviewed on 08/22/2019

	(Contd. of page 1)
H319 Causes se	prious eye irritation.
· Precautionary s	statements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for
	breathing.
P305+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

• NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

120-92-3 Cyclopentanone	65-90%
🐼 Flam. Liq. 3, H226; 🕖 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
107-98-2 1-methoxy-2-propanol	10-15%
🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
· Additional Components:	
102322-80-5 Polyaliphatic imide copolymer Skin Irrit. 2, H315; Eye Irrit. 2A, H319	1-20%
() Skin Irrit. 2. H315: Eve Irrit. 2A. H319	



Safety Data Sheet acc. to OSHA HCS

Printing date 08/22/2019

Reviewed on 08/22/2019

(Contd. of page 2)

0.1-2%

Trade name: LOR B Series Resists

Proprietary Dye B

🗘 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet Water
- · Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

[–] US



Trade name: LOR B Series Resists

(Contd. of page 3)

Reviewed on 08/22/2019

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

Safety Data Sheet acc. to OSHA HCS

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaust at the workplace.
- Prevent formation of aerosols.
- Keep away from heat and direct sunlight.
- Use only under yellow light
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
- Information about storage in one common storage facility: Do not store together with oxidizing and acidic materials. Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Store receptacle in a well ventilated area. Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

- REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm
- TLV Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

[–] US

(Contd. of page 4)



Printing date 08/22/2019

Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/22/2019

Trade name: LOR B Series Resists

- · Respiratory equipment:
- In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
- Protection of hands:



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Form:	Liquid
Color:	Yellow-brown
· Odor:	Sweet
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	120 °C (248 °F)
· Flash point:	30 °C (86 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	2.3 Vol %
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
· Density:	Not determined.
· Relative density	See Table 1 Other Information
· Vapor density	Not determined.
• Evaporation rate	Not determined.



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/22/2019

Trade name: LOR B Series Resists

· Solubility in / Miscibility with	!					
Water:	Water mise	cible No				
Partition coefficient (n-octan	ol/water): Not detern	iined.				
Viscosity:						
Dynamic:	Not detern	iined.				
Kinematic:	Not detern	iined.				
Other information	Table 1. Product specific gravity and VOC data.					
	Name	Number	Sp. Grav.	Vol.(%by wt.) $VOC(g/L)$	
	LOR 0.7B	G316702	0.965	98	40	
	LOR 1B	G316703	0.967	96	930	
	LOR 2B	G316704	0.973	95	930	
	LOR 3B	G316707	0.980	<i>93</i>	920	
	LOR 5B	G316708	0.982	92	910	
	LOR 6B	G316709	0.984	91	900	
	LOR 7B	G316710	0.988	91	900	
	LOR 10B	G316711	0.990	89	880	
	LOR 15B	G316712	0.992	88	870	
	LOR 20B	G316715	1.002	86	860	
	LOR 30B	G316716	1.004	85	850	
	LOR 50B	G316719	1.007	82	830	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products: Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:						
120-92-3 (Cyclopenta	none				
Oral	LD50	1180 mg/kg (Rat)				
Dermal	LD50	>2000 mg/kg (rabbit)				
Inhalative	LC50/4 h	>19.5 mg/l (Rat)				
107-98-21	107-98-2 1-methoxy-2-propanol					
Oral	LD50	5660 mg/kg (Rat)				
		·	10 1			

(Contd. on page 7)

US -



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/22/2019

Trade name: LOR B Series Resists

Dermal		(Contd. of pag
Dermai	LD50	13000 mg/kg (rabbit)
Inhalative	e LC50/4 h	54.6 mg/l (Rat)
102322-8	0-5 Polyalij	phatic imide copolymer
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
	rritant effe	
		to skin and mucous membranes.
•	e: Irritating	<i>•••</i>
		nsitizing effects known. nans: No further relevant information available.
		ical information:
		the following dangers according to internally approved calculation methods for preparatio
Irritant		
· Carcinog	enic catego	ries
-	-	Agency for Research on Cancer)
		nts are listed.
· NTP (Na	tional Toxic	cology Program)
None of the	ie ingredier	nts are listed.
· OSHA-C	ı (Occupati	ional Safety & Health Administration)
NI C.	:	nts are listed.
None of th	ie ingreaiei	
None of t	ie ingreater	
	cal inforn	
2 Ecologi • Toxicity • Aquatic t	cal inform	nation
2 Ecologi • Toxicity • Aquatic to 120-92-3	cal inforn oxicity: Cyclopenta	nation
2 Ecologi • Toxicity • Aquatic to 120-92-3	cal inforn oxicity: Cyclopenta	nation
2 Ecologi • Toxicity • Aquatic to 120-92-3	cal inform oxicity: Cyclopenta h 100 mg/	nation
2 Ecologi • Toxicity • Aquatic t 120-92-3 EC50/48	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg/	nation mone I (daphnia magna) g/l (scenedesmus subspicatus)
2 Ecologi • Toxicity • Aquatic to 120-92-3 EC50/48 EC50/72 LC50/96	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg h >100 mg	nation mone I (daphnia magna) g/l (scenedesmus subspicatus)
2 Ecologi • Toxicity • Aquatic ti 120-92-3 EC50/48 EC50/72 LC50/96 107-98-2	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg h >100 mg 1-methoxy-	nation mone I (daphnia magna) g/l (scenedesmus subspicatus) g/l (fish)
2 Ecologi • Toxicity • Aquatic ti 120-92-3 EC50/48 EC50/72 LC50/96 107-98-2	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg h >100 mg 1-methoxy- hr 23300 m	nation mone I (daphnia magna) g/l (scenedesmus subspicatus) g/l (fish) -2-propanol
2 Ecologi • Toxicity • Aquatic ti 120-92-3 EC50/48 EC50/72 LC50/96 107-98-2	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg h >100 mg 1-methoxy- hr 23300 m >1000 n	nation mone A (daphnia magna) g/l (scenedesmus subspicatus) g/l (fish) -2-propanol ng/l (daphnia magna)
2 Ecologi - Toxicity - Aquatic to 120-92-3 EC50/48 EC50/72 LC50/96 107-98-2 EC50/96 LC50/96 - Persisten	cal inform pxicity: Cyclopenta h 100 mg/ h >100 mg/ h >1000 mg/ h >1	nation mone A (daphnia magna) g/l (scenedesmus subspicatus) g/l (fish) -2-propanol ng/l (daphnia magna) ng/l (green algae) ng/l (Pimephales promelas) radability No further relevant information available.
2 Ecologi - Toxicity - Aquatic to 120-92-3 EC50/48 EC50/72 LC50/96 107-98-2 EC50/96 - Persisten - Behavior	cal inform oxicity: Cyclopenta h 100 mg/ h >100 mg/ h >100 mg/ h >200 mg/ h >200 m h 20800 m ce and degr in environ	nation mone l (daphnia magna) g/l (scenedesmus subspicatus) g/l (fish) -2-propanol ng/l (daphnia magna) ng/l (green algae) ng/l (Pimephales promelas)

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 8)

US

(Contd. of page 7)



Printing date 08/22/2019

Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/22/2019

Trade name: LOR B Series Resists

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1866	
UN proper shipping name DOT, IMDG, IATA ADR	RESIN SOLUTION 1866 RESIN SOLUTION	
Transport hazard class(es)		
DOT		
runner LOX		
Class	3 Flammable liquids	
Label	3	
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	III	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler): EMS Number:	33 F-E,S- <u>E</u>	
Transport in bulk according to Annex		

US —



Safety Data Sheet acc. to OSHA HCS

Printing date 08/22/2019

Reviewed on 08/22/2019

(Contd. of page 8)

Trade name: LOR B Series Resists

· UN ''Model Regulation'':

UN1866, RESIN SOLUTION, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· California SCAQMD Rule 443.1 VOC's: See Table 1 - Section 9

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

— US



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/22/2019

Trade name: LOR B Series Resists

	(Contd. of pag
Hazard pictogra	lms
<u>··</u>	
GHS02 GHS	- 107
01502 015	.07
Signal word Wa	rning
Hazard-determi	ning components of labeling:
Cyclopentanone	
Hazard stateme	
	le liquid and vapor.
H315 Causes sk	
H319 Causes se	rious eye irritation.
Precautionary s	tatements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable.
	breathing.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internatio regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 08/22/2019 / 2

 Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association

(Contd. on page 11)

US



Printing date 08/22/2019

Trade name: LOR B Series Resists

ACGIH: American Conference of Governmental Industrial Hygienists	(Contd. of page 10)
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flam. Liq. 3: Flammable liquids – Category 3	
Shin Irrit 2: Shin correspondir ritation Category 2	

Safety Data Sheet acc. to OSHA HCS

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Reviewed on 08/22/2019