

Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: LOR C Series Resists
- · Article number: G713708, G713711, G713713, G713714, G713716
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from: Product Safety
Email: productsafety@kayakuAM.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard



H361 Suspected of damaging fertility or the unborn child.

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

^{: 2)} – EU



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

	(Contd. of page 1)
2.2 Label ele	ments
Labelling ac	cording to Regulation (EC) No 1272/2008
The product	is classified and labelled according to the CLP regulation.
Hazard picto	grams
$\mathbf{\wedge}$	$\wedge \wedge \wedge$
July /	
GHS02 C	HS05 GHS07 GHS08
Signal word	Danger
	mining components of labelling:
Cyclopentan	
gamma-Buty	
	rfuryl alcohol
Hazard state	
	Flammable liquid and vapour.
	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361	Suspected of damaging fertility or the unborn child.
	May cause drowsiness or dizziness.
Precautional	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position
D205 . D251	comfortable for breathing.
P305+P351-	-P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i
1222 J 222	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internationa
	regulations.
2.3 Other ha	
	3T and vPvB assessment
PBT: Not ap	plicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

⁻ EU -



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

Dangerous components:		
CAS: 120-92-3	Cyclopentanone	40-60%
EINECS: 204-435-9	🚸 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Index number: 606-025-00-9		
CAS: 96-48-0	gamma-Butyrolactone	25-50%
EINECS: 202-509-5	🚸 Eye Dam. 1, H318; 🐠 Acute Tox. 4, H302; STOT SE 3, H336	
CAS: 102322-80-5	Polyaliphatic imide copolymer	5-20%
	𝔆 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 97-99-4	Tetrahydrofurfuryl alcohol	1-5%
EINECS: 202-625-6	🗞 Repr. 2, H361; 🕔 Acute Tox. 4, H302; Eye Irrit. 2, H319	
Index number: 603-061-00-7		
	Proprietary Dye B	<1%
	🕐 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents:
- Water with full jet
- Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 4)



Printing date 22.08.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. Use only under yellow light
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and containers:* Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

- · Information about storage in one common storage facility:
- Do not store together with alkalis (caustic solutions).
- Do not store together with oxidising and acidic materials.
- Further information about storage conditions:
- Store in cool, dry conditions in well sealed containers.
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

⁻ EU



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

(Contd. of page 4)

· 8.2 Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. · Respiratory protection: In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves Nitrile rubber, NBR · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection: Tightly sealed goggles

9.1 Information on basic physical a General Information	nd chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Yellow-brown	
Odour:	Sweetish	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	unge: 130 °C	
Flash point:	30 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	430 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

	(Contd. of page 5
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.7 Vol %
Upper:	15.6 Vol %
• Vapour pressure at 20 °C:	1 hPa
· Density:	Not determined
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Partly miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- \cdot 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

120-92-3 (Cyclopenta	none
Oral	LD50	1180 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)

96-48-0 gamma-Butyrolactone

Oral	LD50	1540 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (gui)
Inhalative	LC50/4 h	>5.1 mg/l (Rat)
		(Contd. on page 7)

- EU



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

(Contd. of page 6)

Trade name: LOR C Series Resists

Oral LD50 1600 mg/kg (Rat)	
 Primary irritant effect: Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye damage. Respiratory or skin sensitisation Based on available data. Experience with humans: No further relevant informatio CMR effects (carcinogenity, mutagenicity and toxicity f Germ cell mutagenicity Based on available data, the cla Carcinogenicity Based on available data, the classificati Reproductive toxicity Suspected of damaging fertility or the unborn child. STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure Based on available data, the classificati 	on available. Tor reproduction) ssification criteria are not met. Ton criteria are not met. lassification criteria are not met.
• Aspiration hazara Based on available data, the classifica	ation criteria are not met.
SECTION 12: Ecological information	
· 12.1 Toxicity	
· Aquatic toxicity:	
120-92-3 Cyclopentanone	
EC50/48 h 100 mg/l (daphnia magna)	
EC50/72 h >100 mg/l (scenedesmus subspicatus)	
LC50/96 h > 100 mg/l (fish)	
96-48-0 gamma-Butyrolactone	
EC50/17 h >10000 mg/l (bacterium)	
EC50/48 h > 500 mg/l (daphnia magna)	
EC50/48 h >500 mg/l (daphnia magna) EC50/72 h 360 mg/l (green algae)	

(Contd. on page 8)

EU



Printing date 22.08.2019

Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name	RESIN SOLUTION	
ADR, IMDG, IATA	RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
3		
Class Label	3 Flammable liquids. 3	
	5	
14.4 Packing group ADR, IMDG, IATA	111	
	111	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Danger code (Kemler):	Warning: Flammable liquids. 30	
EMS Number:	F-E,S-D	
14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	

(Contd. on page 9)



Version number 3

Revision: 22.08.2019

Trade name: LOR C Series Resists

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. · Classification according to Regulation (EC) No 1272/2008 Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuAM) · Revision History: The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated. · Abbreviations and acronvms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

EI.