

Printing date 08/22/2019

Reviewed on 08/22/2019

1 Identification

- **Product identifier**
- **Trade name:** LOR C Series Resists
- **Product number:** G713708, G713711, G713713, G713714, G713716
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Information department:**
 Product Safety
 Email: productsafety@kayakuAM.com
- **Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS05 GHS07 GHS08

· Signal word Danger
· Hazard-determining components of labeling:

Cyclopentanone

gamma-Butyrolactone

Tetrahydrofurfuryl alcohol

· Hazard statements

H226 Flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 3

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = *3

Fire = 3

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

(Contd. on page 3)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

 · **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

 · **Chemical characterization:** Mixtures

 · **Description:** Mixture of the substances listed below with nonhazardous additions.

 · **Dangerous components:**

120-92-3	Cyclopentanone ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	40-60%
96-48-0	gamma-Butyrolactone ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; STOT SE 3, H336	25-50%
102322-80-5	Polyaliphatic imide copolymer ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	5-20%
97-99-4	Tetrahydrofurfuryl alcohol ⚠ Repr. 2, H361; ⚠ Acute Tox. 4, H302; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	1-5%
	Proprietary Dye B ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	<1%

4 First-aid measures

 · **Description of first aid measures**

 · **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

 · **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

 · **After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

 · **After swallowing:**

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

 · **Information for doctor:**

 · **Most important symptoms and effects, both acute and delayed** No further relevant information available.

 · **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

 · **Extinguishing media**

 · **Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

 · **For safety reasons unsuitable extinguishing agents:**

Water with full jet

(Contd. on page 4)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 3)

Water

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Use only under yellow light

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and containers:**

Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

- **Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

- **Further information about storage conditions:**

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 4)

 · **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**

97-99-4 Tetrahydrofurfuryl alcohol

WEEL 0.5 ppm

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

 · **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material** Contact glove manufacture for break-through time.

 · **Eye protection:**


Tightly sealed goggles

9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form: Liquid

Color: Yellow-brown

 · **Odor:** Sweet

 · **Odor threshold:** Not determined.

 · **pH-value:** Not determined.

 · **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 130 °C (266 °F)

 · **Flash point:** 30 °C (86 °F)

 · **Flammability (solid, gaseous):** Not applicable.

 · **Ignition temperature:** 430 °C (806 °F)

 · **Decomposition temperature:** Not determined.

(Contd. on page 6)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 5)

· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.7 Vol %
Upper:	15.6 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Partly miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
120-92-3 Cyclopentanone		
Oral	LD50	1180 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)
96-48-0 gamma-Butyrolactone		
Oral	LD50	1540 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (gui)
Inhalative	LC50/4 h	>5.1 mg/l (Rat)

(Contd. on page 7)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 6)

97-99-4 Tetrahydrofurfuryl alcohol

Oral	LD50	1600 mg/kg (Rat)
------	------	------------------

· Primary irritant effect:
· on the skin: Irritant to skin and mucous membranes.

· on the eye: Irritating effect.

· Sensitization: No sensitizing effects known.

· Experience with humans: No further relevant information available.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories
· IARC (International Agency for Research on Cancer)

96-48-0	gamma-Butyrolactone	3
---------	---------------------	---

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information
· Toxicity
· Aquatic toxicity:
120-92-3 Cyclopentanone

EC50/48 h	100 mg/l (daphnia magna)
-----------	--------------------------

EC50/72 h	>100 mg/l (scenedesmus subspicatus)
-----------	-------------------------------------

LC50/96 h	>100 mg/l (fish)
-----------	------------------

96-48-0 gamma-Butyrolactone

EC50/17 h	>10000 mg/l (bacterium)
-----------	-------------------------

EC50/48 h	>500 mg/l (daphnia magna)
-----------	---------------------------

EC50/72 h	360 mg/l (green algae)
-----------	------------------------

LC50/96 h	>220 - <460 mg/l (golden orfe)
-----------	--------------------------------

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:
· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:
· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

US

(Contd. on page 8)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.
 Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1866
· UN proper shipping name	
· DOT, ADR	Resin solution
· IMDG, IATA	RESIN SOLUTION
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1866, Resin solution, 3, III

US

(Contd. on page 9)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 8)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- Proposition 65

• Chemicals known to cause cancer:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

• Carcinogenic categories

• EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

• Massachusetts State Right To Know List

120-92-3 Cyclopentanone

97-99-4 Tetrahydrofurfuryl alcohol

• New Jersey State Right To Know List

120-92-3 Cyclopentanone

• Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

97-99-4 Tetrahydrofurfuryl alcohol

- California SCAQMD Rule 443.1 VOC's: No information available.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02 GHS05 GHS07 GHS08

- Signal word Danger

(Contd. on page 10)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 9)

· Hazard-determining components of labeling:

 Cyclopentanone
 gamma-Butyrolactone
 Tetrahydrofurfuryl alcohol

· Hazard statements

 H226 Flammable liquid and vapor.
 H302+H332 Harmful if swallowed or if inhaled.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H361 Suspected of damaging fertility or the unborn child.
 H336 May cause drowsiness or dizziness.

· Precautionary statements

 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P302+P352 If on skin: Wash with plenty of soap and water.
 P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
 P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
 P370+P378 In case of fire: Use for extinction: Carbon dioxide.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department
· Contact: Tom Cole, EHS Manager (tcole@kayakuAM)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 08/22/2019 / 2

· Abbreviations and acronyms:

 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Printing date 08/22/2019

Reviewed on 08/22/2019

Trade name: LOR C Series Resists

(Contd. of page 10)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

US