

Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PMGI SF Series Resists
- · Article number:

G113101, G113102, G113103, G113104, G113105, G113106, G113107, G113175, G113108, G113109, G113110, G113111, G113112, G113113, G113114, G113115, G113117, G113119, G113123

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

(Contd. of page 1)

· Hazard pictograms







GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Tetrahydrofurfuryl alcohol

Cyclopentanone

· Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.* P370+P378 In case of fire: Use for extinction: Alcohol resistant foam. P370+P378 *In case of fire: Use for extinction: Fire-extinguishing powder.*

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 120-92-3	Cyclopentanone	65-85%
EINECS: 204-435-9	\delta Flam. Liq. 3, H226; 伙 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Index number: 606-025-00-9		
CAS: 97-99-4 T	Tetrahydrofurfuryl alcohol	1-15%
EINECS: 202-625-6	🗞 Repr. 2, H361; 🕔 Acute Tox. 4, H302; Eye Irrit. 2, H319	
Index number: 603-061-00-7		

(Contd. on page 3)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

	(Co	ntd. of page 2)
CAS: 102322-80-5	Polyaliphatic imide copolymer	1-25%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
· Additional Components:		
Proprietary surfactant		<1%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

(Contd. of page 3)

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Keep receptacles tightly sealed.

Use only under yellow light

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

(Contd. of page 4)

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Odour:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

Form: Liquid

Colour: According to product specification

Sweetish

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 130-180 °C

· Flash point: 30 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 280 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol %
Upper: Not determined.

· Vapour pressure at 20 °C: 0.3 hPa

Density: Not determined.Vapour density Not determined.

(Contd. on page 6)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

						(Contd. of page :
· Evaporation rate	Not de	etermined.				
· Solubility in / Miscibility with						
water:	Slight	ly soluble.				
· Partition coefficient: n-octanol/water:	Not de	etermined.				
· Viscosity:						
Dynamic:	Not de	etermined.				
Kinematic:	Not de	etermined.				
· 9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by wt.	VOC(g/L)	
	SF1	G113101	0.966	99	955	
	SF2	G113102	0.968	98	950	
	SF3	G113103	0.970	97	945	
	SF4	G113104	0.973	96	935	
	SF5	G113105	0.975	95	930	
	SF6	G113106	0.980	94	920	
	SF7	G113107	0.981	93	915	
	SF7.5	G113175	0.983	92.5	910	
	SF8	G113108	0.984	92	905	
	SF9	G113109	0.985	91	900	
	SF10	G113110	0.988	90	890	
	SF11	G113111	0.992	89	880	
	SF12	G113112	0.996	87.5	870	
	SF13	G113113	0.998	87	860	
	SF14	G113114	1.001	86	865	
	SF15	G113115	1.003	85	850	
	SF17	G113117	1.008	82.5	830	
	SF19	G113119	1.012	81	820	
	SF23	G113123	1.023	<i>77</i>	<i>785</i>	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed.

	0 values re	evant for classification:
120-92-3	3 Cyclopeni	anone
Oral	LD50	1180 mg/kg (Rat)
•	•	(Contd on page 7)

(Contd. on page 7)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

		(Contd. of page 6)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)
97-99-4 Te	trahydrofi	urfuryl alcohol
Oral	LD50	800 mg/kg (Guinea pig)
		2300 mg/kg (mouse)
		1600 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (Guinea pig)
102322-80	-5 Polyalip	phatic imide copolymer
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging fertility or the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

	· Aquatic tox	ricity:
	120-92-3 C	yclopentanone
	EC50/48 h	100 mg/l (daphnia magna)
	EC50/72 h	>100 mg/l (scenedesmus subspicatus)
L	LC50/96 h	>100 mg/l (fish)

- 12.2 Persistence and degradability Moderately /partly biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	tion	
14.1 UN-Number ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group ADR, IMDG, IATA	III	
<u> </u>	111	
14.5 Environmental hazards: Marine pollutant:	No	
<u> </u>		
14.6 Special precautions for user Danger code (Kemler):	Warning: Flammable liquids. 33	
EMS Number:	F-E,S-D	
14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)



Printing date 09.09.2019 Version number 4 Revision: 09.09.2019

Trade name: PMGI SF Series Resists

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2