

Printing date 09/09/2019 Reviewed on 09/09/2019

## 1 Identification

· Product identifier

· Trade name: PMGI SFG Fast Series Resists

· Product number: G312101, G312102

· Application of the substance / the mixture Photoresist

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kayaku Advanced Materials

200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

**Product Safety** 

Email: productsafety@kayakuAM.com

· Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 1)

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.* P370+P378 In case of fire: Use for extinction: Alcohol resistant foam. *In case of fire: Use for extinction: Fire-extinguishing powder.* P370+P378

P370+P378 *In case of fire: Use for extinction: Carbon dioxide.* 

Store in a well-ventilated place. Keep cool. P403+P235

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components:                                        |        |  |
|----------------------------------------------------------------|--------|--|
|                                                                | 65-85% |  |
| Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2A, H319 |        |  |
| 107-98-2                                                       | 1-15%  |  |
| ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336                        |        |  |
| · Additional Components:                                       |        |  |

102322-80-5 Polyaliphatic imide copolymer

🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H319

1-25%

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 2)

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

#### · After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

#### · Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

*See Section 8 for information on personal protection equipment.* 

(Contd. on page 4)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 3)

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep receptacles tightly sealed.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in a cool location.

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| · Components with limit values that re | equire monitoring a | t the workplace: |
|----------------------------------------|---------------------|------------------|
|----------------------------------------|---------------------|------------------|

#### 107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 553 mg/m³, 150 ppm Long-term value: 369 mg/m³, 100 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

(Contd. on page 5)

(Contd. of page 4)



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

| 9 Physical  | and c  | hemical        | nronerties |
|-------------|--------|----------------|------------|
| / I hysical | unu ci | <i>temueut</i> | properties |

| · Information on basic physical and chemical properties<br>· General Information |                                                                                            |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| · Appearance:                                                                    |                                                                                            |
| Form:                                                                            | Liquid                                                                                     |
| Color:                                                                           | Clear to light yellow                                                                      |
| · Odor:                                                                          | Slightly sweet                                                                             |
| · Odor threshold:                                                                | Not determined.                                                                            |
| · pH-value:                                                                      | Not determined.                                                                            |
| · Change in condition                                                            |                                                                                            |
| Melting point/Melting range:                                                     | Undetermined.                                                                              |
| Boiling point/Boiling range:                                                     | 120 °C (248 °F)                                                                            |
| · Flash point:                                                                   | 30 °C (86 °F)                                                                              |
| · Flammability (solid, gaseous):                                                 | Not applicable.                                                                            |
| · Ignition temperature:                                                          | 270 °C (518 °F)                                                                            |
| · Decomposition temperature:                                                     | Not determined.                                                                            |
| · Auto igniting:                                                                 | Product is not selfigniting.                                                               |
| · Danger of explosion:                                                           | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits:                                                              |                                                                                            |
| Lower:                                                                           | 2.3 Vol %                                                                                  |
| Upper:                                                                           | Not determined.                                                                            |
| · Vapor pressure at 20 °C (68 °F):                                               | 12 hPa (9 mm Hg)                                                                           |
| · Density:                                                                       | Not determined.                                                                            |
| · Relative density                                                               | See Table 1 Other Information                                                              |
| · Vapor density                                                                  | Not determined.                                                                            |
| · Evaporation rate                                                               | Not determined.                                                                            |
| · Solubility in / Miscibility with                                               |                                                                                            |
| Water:                                                                           | Water miscible No                                                                          |

(Contd. on page 6)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 5)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

**VOC content:** See Table 1 below

• Other information Table 1. Product specific gravity and VOC data.

Name Number Sp. Grav. Vol.(%by wt.) VOC(g/L) SFG 1F G312101 0.950 99 940 SFG 2F G312102 0.960 98 940

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 1 | · LD/LC50 values that are relevant for classification: |                                                               |  |
|-------------|--------------------------------------------------------|---------------------------------------------------------------|--|
| 120-92-3 (  | 120-92-3 Cyclopentanone                                |                                                               |  |
| Oral        | LD50                                                   | 1180 mg/kg (Rat)                                              |  |
| Dermal      | LD50                                                   | >2000 mg/kg (rabbit)                                          |  |
| Inhalative  | LC50/4 h                                               | >19.5 mg/l (Rat)                                              |  |
| 107-98-2 1  | 107-98-2 1-methoxy-2-propanol                          |                                                               |  |
| Oral        | LD50                                                   | 5660 mg/kg (Rat)                                              |  |
| Dermal      | LD50                                                   | 13000 mg/kg (rabbit)                                          |  |
| Inhalative  | LC50/4 h                                               | 54.6 mg/l (Rat)                                               |  |
| 102322-80   | 102322-80-5 Polyaliphatic imide copolymer              |                                                               |  |
| Oral        | LD50                                                   | >5000 mg/kg (Rat) (Data for compositionally similar material) |  |
| Dermal      | LD50                                                   | >5000 mg/kg (Rat) (Data for compositionally similar material) |  |

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 6)

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

## 12 Ecological information

· Toxicity

| · Aquatic toxi | · Aquatic toxicity:                 |  |  |
|----------------|-------------------------------------|--|--|
| 120-92-3 Cy    | 120-92-3 Cyclopentanone             |  |  |
| EC50/48 h      | 100 mg/l (daphnia magna)            |  |  |
| EC50/72 h      | >100 mg/l (scenedesmus subspicatus) |  |  |
| LC50/96 h      | >100 mg/l (fish)                    |  |  |
| 107-98-2 1-1   | 107-98-2 1-methoxy-2-propanol       |  |  |
| EC50/96 hr     | 23300 mg/l (daphnia magna)          |  |  |
|                | >1000 mg/l (green algae)            |  |  |
| LC50/96 h      | 20800 mg/l (Pimephales promelas)    |  |  |

- · Persistence and degradability Moderately /partly biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 7)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

| 14 Transport information                                |                                       |  |
|---------------------------------------------------------|---------------------------------------|--|
| · UN-Number<br>· DOT, ADR, IMDG, IATA                   | UN1866                                |  |
| · UN proper shipping name<br>· DOT, IMDG, IATA<br>· ADR | RESIN SOLUTION<br>1866 RESIN SOLUTION |  |
| · Transport hazard class(es)<br>· DOT                   |                                       |  |
| a malicas (Car)                                         |                                       |  |
| · Class                                                 | 3 Flammable liquids                   |  |

3

· ADR, IMDG, IATA



 $\cdot \textit{Label}$ 

| · Class<br>· Label                                                                                   | 3 Flammable liquids<br>3                            |
|------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| · Packing group<br>· DOT, ADR, IMDG, IATA                                                            | III                                                 |
| Environmental hazards: Marine pollutant:                                                             | No                                                  |
| <ul> <li>Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> </ul> | Warning: Flammable liquids<br>33<br>F-E, <u>S-E</u> |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.            |                                                     |

UN1866, RESIN SOLUTION, 3, III

## 15 Regulatory information

· UN "Model Regulation":

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Contd. on page 9)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 8)

### · Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65

#### · Chemicals known to cause cancer:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

#### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients are listed.

#### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

#### · Massachusetts State Right To Know List

120-92-3 Cyclopentanone

107-98-2 | 1-methoxy-2-propanol

### · New Jersey State Right To Know List

120-92-3 Cyclopentanone

#### · Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 10)



Printing date 09/09/2019 Reviewed on 09/09/2019

Trade name: PMGI SFG Fast Series Resists

(Contd. of page 9) P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 If swallowed: Immediately call a poison center/doctor. P302+P352 If on skin: Wash with plenty of soap and water. P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: Alcohol resistant foam. P370+P378 P370+P378 *In case of fire: Use for extinction: Fire-extinguishing powder.* P370+P378 *In case of fire: Use for extinction: Carbon dioxide.* P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- · Date of preparation / last revision 09/09/2019 / 1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

 $Flam.\ Liq.\ 3:\ Flammable\ liquids-Category\ 3$ 

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3