

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PermiNex® 1000 Series Resists
- **Article number:** Y514020, Y514046, Y514058, Y514062
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use SU16** Manufacture of computer, electronic and optical products, electrical equipment
- **Application of the substance / the mixture** Photoresist
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Kayaku Advanced Materials  
 200 Flanders Road  
 Westborough, MA 01581  
 Tel: (617) 965-5511  
 Fax: (617) 965-5818
- **Further information obtainable from:**  
 Product Safety  
 Email: [productsafety@kayakuAM.com](mailto:productsafety@kayakuAM.com)
- **1.4 Emergency telephone number:**  
 Kayaku Advanced Materials : 617-965-5511  
 Chemtrec USA Emergency : 800-424-9300 (24 hr)  
 Chemtrec International Emergency : 703-527-3887 (24 hr)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

 Skin Irrit. 2      H315 Causes skin irritation.  
 Eye Irrit. 2      H319 Causes serious eye irritation.  
 Skin Sens. 1      H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 1)

**· Hazard pictograms**


GHS02 GHS07 GHS09

**· Signal word** Warning

**· Hazard-determining components of labelling:**

Epoxy Resin M3

**· Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

55.6 % of the mixture consists of component(s) of unknown toxicity.



Contains 84.9 % of components with unknown hazards to the aquatic environment.

**· 2.3 Other hazards**
**· Results of PBT and vPvB assessment**
**· PBT:** Not applicable.

**· vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**
**· 3.2 Chemical characterisation: Mixtures**
**· Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

	Epoxy Resin M3  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	40-60%
--	---	--------

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2019

Version number 2

Revision: 09.09.2019

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 2)

	Epoxy Resin M2 ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9	Cyclopentanone ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-25%
	Adhesion Promoter ⚠ Eye Dam. 1, H318	1-5%
	Proprietary Quencher ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	1-5%

**· Additional Components:**

Proprietary Photoacid Generator

1-5%

**· Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**· 4.1 Description of first aid measures**
**· General information:** Immediately remove any clothing soiled by the product.

**· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**· After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

**· After swallowing:** If symptoms persist consult doctor.

**· 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**· 4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### SECTION 5: Firefighting measures

**· 5.1 Extinguishing media**
**· Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

**· For safety reasons unsuitable extinguishing agents:**

Water with full jet

Water

**· 5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**· 5.3 Advice for firefighters**
**· Protective equipment:** Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 3)

*Ensure adequate ventilation**Keep away from ignition sources.*

- **6.2 Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*

- **6.3 Methods and material for containment and cleaning up:**

*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Ensure adequate ventilation.**Do not flush with water or aqueous cleansing agents*

- **6.4 Reference to other sections**

*See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.*

## **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**

*Ensure good ventilation/exhaust at the workplace.**Prevent formation of aerosols.*

- **Information about fire - and explosion protection:**

*Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.**Use explosion-proof apparatus / fittings and spark-proof tools.*

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and containers:**

*Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.*

- **Information about storage in one common storage facility:**

*Do not store together with oxidising and acidic materials.**Do not store together with alkalis (caustic solutions).*

- **Further information about storage conditions:**

*Store in cool, dry conditions in well sealed containers.**Protect from heat and direct sunlight.**Store receptacle in a well ventilated area.*

- **7.3 Specific end use(s)** *No further relevant information available.*

## **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** *No further data; see item 7.*

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

*The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

- **Additional information:** *The lists valid during the making were used as basis.*

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

*Keep away from food and beverages.**Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Avoid contact with the eyes and skin.*

(Contd. on page 5)

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 4)

· **Respiratory protection:**

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	130 °C

· **Flash point:** 30 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 430 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.3 Vol %
Upper:	0.0 Vol %

· **Vapour pressure at 20 °C:** 11 hPa

· **Density:** Not determined.

· **Relative density** Not determined.

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2019

Version number 2

Revision: 09.09.2019

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 5)

· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	58.1 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic polymerisation.
- **10.4 Conditions to avoid**  
Heat, flames and sparks. Extremes of temperature and direct sunlight.  
Contact with incompatible materials.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Corrosive gases/vapours  
Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### **Epoxy Resin M2**

Oral	LD50	>2000 mg/kg (Rat)
------	------	-------------------

##### **Adhesion Promoter**

Oral	LD50	8030 mg/kg (Rat)
Dermal	LD50	4248 mg/kg (Rat)
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)

##### **120-92-3 Cyclopentanone**

Oral	LD50	1820 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)

(Contd. on page 7)



**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 6)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### Adhesion Promoter

LC50/96 h	55 mg/l (Cyprinus carpio (common carp))
EC50/48 h	30 mg/l (daphnia magna)
EC50/72 h	255 mg/l (Desmodesmus subscipatus (green algae))

##### 120-92-3 Cyclopentanone

LC50/48 hr	2950 mg/L (golden orfe)
LC50/96 h	>100 mg/l (fish)
EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made in accordance with International, National, and regional regulations.

(Contd. on page 8)

Printing date 09.09.2019

Version number 2


Revision: 09.09.2019

**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UN1866
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	RESIN SOLUTION
· <b>IMDG</b>	RESIN SOLUTION, MARINE POLLUTANT
· <b>IATA</b>	Resin solution
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	Product contains environmentally hazardous substances: Formaldehyde, polymer with 1-chloro-2,3-epoxypropane and phenol
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E, <u>S-E</u>
· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)



**Trade name: PermiNex® 1000 Series Resists**

(Contd. of page 8)

· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
   E2 Hazardous to the Aquatic Environment  
   P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
   H226 Flammable liquid and vapour.  
   H302 Harmful if swallowed.  
   H315 Causes skin irritation.  
   H317 May cause an allergic skin reaction.  
   H318 Causes serious eye damage.  
   H319 Causes serious eye irritation.  
   H335 May cause respiratory irritation.  
   H411 Toxic to aquatic life with long lasting effects.  
   H412 Harmful to aquatic life with long lasting effects.
- **Classification according to Regulation (EC) No 1272/2008**  
   Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.
- **Department issuing SDS:** Product safety department
- **Contact:** Tom Cole, EHS Manager (tcole@kayakuAM)
- **Revision History:**  
   The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.
- **Abbreviations and acronyms:**  
   ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
   IMDG: International Maritime Code for Dangerous Goods  
   IATA: International Air Transport Association  
   GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
   EINECS: European Inventory of Existing Commercial Chemical Substances  
   ELINCS: European List of Notified Chemical Substances  
   CAS: Chemical Abstracts Service (division of the American Chemical Society)  
   LC50: Lethal concentration, 50 percent  
   LD50: Lethal dose, 50 percent  
   PBT: Persistent, Bioaccumulative and Toxic  
   vPvB: very Persistent and very Bioaccumulative  
   Flam. Liq. 3: Flammable liquids – Category 3  
   Acute Tox. 4: Acute toxicity – Category 4  
   Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 10)

***Safety data sheet***  
***according to 1907/2006/EC, Article 31***

Printing date 09.09.2019

Version number 2

Revision: 09.09.2019

***Trade name: PermiNex® 1000 Series Resists****Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

(Contd. of page 9)

EU