

Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: EP-600 Two Part Conductive Epoxy A-SIDE
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Functional electronic epoxy component
- \cdot 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Applied Ink Solutions 200 Flanders Road Westborough, MA 01581

USA

- Further information obtainable from: sales@appliedinksolutions.com • 1.4 Emergency telephone number:
- Applied Ink Solutions : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

GHS08 health hazard

Muta. 2H341 Suspected of causing genetic defects.Carc. 2H351 Suspected of causing cancer.

GHS09 environment

Aquatic Acute 1H400Very toxic to aquatic life.Aquatic Chronic 1H410Very toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • *Hazard pictograms*



(Contd. on page 2)

EU



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

rning (Contd. of page 2	
ning components of labelling:	
with formaldehyde, glycidyl ether	
her	
n	
its	
n irritation.	
rious eye irritation.	
e an allergic skin reaction.	
of causing genetic defects.	
of causing cancer.	
to aquatic life with long lasting effects.	
tatements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Avoid breathing dust/fume/gas/mist/vapours/spray.	
Wash thoroughly after handling.	
Contaminated work clothing should not be allowed out of the workplace.	
Avoid release to the environment.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
IF ON SKIN: Wash with plenty of water.	
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a positio comfortable for breathing.	
38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.	
If skin irritation or rash occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Store in a well-ventilated place. Keep container tightly closed.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
ds	
and vPvB assessment	

• *PB1*: Not applicable. • *vPvB*: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 7440-22-4	Silver	75-100%
EINECS: 231-131-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 28064-14-4	Phenol, polymer with formaldehyde, glycidyl ether	5-15%
	Aquatic Acute 1, H400; Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 2426-08-6	Butyl glycidyl ether	1-5%
EINECS: 219-376-4	🚯 Flam. Liq. 3, H226; 🚸 Muta. 2, H341; Carc. 2, H351; 🕔 Acute	
Index number: 603-039-00-7	Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, U225; Acute Chronic 2, U412	
	H335; Aquatic Chronic 3, H412	td. on page 3



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

	(Cor	itd. of page 2)
Proprietary Resin		<1%
Aquatic Chronic 2, H411; 🗘 Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
6.2 Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
· 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
San Section 12 for disposal information

See Section 13 for disposal information.

(Contd. on page 4)



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

(Contd. of page 3)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions).
- Do not store together with oxidising and acidic materials.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from food and beverages.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- **Respiratory protection:**

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- *Eye protection: Goggles recommended during refilling*

(Contd. on page 5)



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

(Contd. of page 4)

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

SECTION 9: Physical and chemi	ical properties	
9.1 Information on basic physical and c	chemical properties	
General Information		
Appearance:		
Form:	Thick liquid	
Colour: Odour:	Silver-coloured Sweetish	
Odour: Odour threshold:	Sweensn Not determined.	
pH-value:	Not determined.	
•		
Change in condition Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	• • • • • • • • • • • • • • • • • • • •	
0.000		
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	96.4 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

EU -



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

· 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

2426-08-6 Butyl glycidyl ether

Oral LD50 2050 mg/kg (Rat)

Dermal LD50 2520 mg/kg (rabbit)

· Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

 \cdot Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity

Suspected of causing genetic defects.

· Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

28064-14-4 Pheno	ol, polymer with formaldehyde, glycidyl ether
EC50/48 h	1-10 mg/l (daphnia magna)

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill)) 0.00155-0.00293 mg/l (Pimephales promelas)

• 12.2 Persistence and degradability No further relevant information available.

• 12.2 I ersistence and degradability No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Ecotoxical effects:

• **Remark:** Toxic for fish

• Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

(Contd. on page 7)

EU -



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

(Contd. of page 6) Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR, IATA IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE N.O.S. (Silver, Phenol, polymer with formaldehyde, glycidy ether) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE N.O.S. (Silver, Phenol, polymer with formaldehyde, glycidy ether), MARINE POLLUTANT
14.3 Transport hazard class(es) ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances Silver, Phenol, polymer with formaldehyde, glycidyl ether
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles. 90



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

14.7 Transport in bulk according to Anno Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE
0	LIQUID, N.O.S. (SILVER, PHENOL, POLYMER WIT
	FORMALDEHYDE, GLYCIDYL ETHER), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

• Other regulations, limitations and prohibitive regulations

RoHS (*EU*)2015/863 along with *EU* Directive 2022/19/*EU* – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Mercury (Hg); Lead (Pb); Hexavalent chromium (Cr6+); Polybrominated biphenyls (PBB); Polybrominated diphenyl ethers (PBDE); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DBP); Diisobutyl phthalate (DIBP).

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product does not contain substances on the SVHC list. • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

EU



Printing date 07.11.2019

Version number 2

Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - A-SIDE

(Contd. of page 8)

FU

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H341 Suspected of causing genetic defects. H351 Suspected of causing cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuAM) · Revision History: The hazard classification and precautionary statements for the mixture in Section 2 were revised. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3