

Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: EP-600 Two Part Conductive Epoxy B-SIDE
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Functional electronic epoxy curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Applied Ink Solutions

200 Flanders Road

Westborough, MA 01581

USA

- · Further information obtainable from: sales@appliedinksolutions.com
- · 1.4 Emergency telephone number:

Applied Ink Solutions: 617-965-5511

Chemtrec USA Emergency: 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Fatty acids, tall-oil, reaction products with tetraethylenepentamine Tetraethylenepentamine

· Hazard statements

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	75-100%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 112-57-2	Tetraethylenepentamine	5-15%
EINECS: 203-986-2 Index number: 612-060-00-0	Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

(Contd. on page 4)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 3)

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Amber coloured
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Alkaline

(Contd. on page 5)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

	(Contd. of page
· Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 333 °C
· Flash point:	195 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not determined.
 Density: Relative density Vapour density Evaporation rate 	Not determined. Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents:	0.0 %
Solids content: · 9.2 Other information	100.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Ammonia



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

112-57-2 Tetraethylenepentamine

Dermal LD50 660 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

 ${\it Must not reach sewage water or drainage ditch undiluted or unneutralised}.$

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 6)

Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	Not Regulated	
ADN	Void	
14.2 UN proper shipping name		
ADR, ADN	Void	
IMDG, IATA	Not Regulated	
· 14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class	Not Regulated	
ADN/R Class:	Void	
14.4 Packing group		
ADR, IMDG, IATA	Not Regulated	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Other regulations, limitations and prohibitive regulations

RoHS (EU)2015/863 along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Mercury (Hg); Lead (Pb); Hexavalent chromium (Cr6+); Polybrominated biphenyls (PBB); Polybrominated diphenyl ethers (PBDE); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DBP); Diisobutyl phthalate (DIBP).

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product does not contain substances on the SVHC list.

(Contd. on page 8)



Printing date 07.11.2019 Version number 2 Revision: 07.11.2019

Trade name: EP-600 Two Part Conductive Epoxy - B-SIDE

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $LC50: Lethal\ concentration,\ 50\ percent$

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 3$