Printing date 1/24/2017 Reviewed on 1/24/2017

1 Identification of the substance/mixture and of the company

- · Product identifier
- · Trade name: AG-610 Silver Conductive Ink
- · Application of the substance / the mixture Functional electronic printing ink
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Applied Ink Solutions 17 Hampshire Drive, Unit 8 Hudson, NH 03051 USA

· Information department:

Product Safety

Email: sales@appliedinksolutions.com

· Emergency telephone number:

Chemtrec USA Emergency: 800-424-9300

Chemtrec International Emergency: 703-527-3887

Applied Ink Solutions : 603-595-6221

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

IS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labeling:
- n-Butyl acetate
- · Hazard statements

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 1)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.* P370+P378 In case of fire: Use for extinction: Alcohol resistant foam. P370+P378 *In case of fire: Use for extinction: Fire-extinguishing powder.*

P370+P378 In case of fire: Use for extinction: Carbon dioxide. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	· Dangerous	components:		
	7440-22-4	Silver	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	40-60%
	123-86-4	n-Butyl acetate	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	25-50%
Ī	· Additional	Components:		

Proprietary polyester 5-15%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 3)

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	· Components with limit values that require monitoring at the workplace:	
123-8	86-4 n-Butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
	Short-term value: 950 mg/m³, 200 ppm	
	Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm	

· Additional information: The lists that were valid during the creation were used as basis.

Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 4)

Physical and chemical proper	rties
· Information on basic physical and · General Information	chemical properties
· Appearance: Form: Color: · Odor: · Odor threshold:	Liquid Silver-brown Sweet Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 124°C (255°F)
· Flash point:	27 °C (81 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	1.24 g/cm³ (14.40 lbs/gal) Not determined. Not determined. 1.6-2.3 (BuAc=1)
· Solubility in / Miscibility with Water:	Water miscible No
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC content:	40.0 % 40.0 %
Solids content: Other information	60.0 % No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal use conditions
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	LD/LC30 values that are relevant for classification:		
123-86-4 n	ı-Butyl ace	utyl acetate	
Oral	LD50	13100 mg/kg (Rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21.0 mg/l (Rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:	
7440-22-4 Silver	
LC50/96 h (static)	0.0062 mg/l (Lepomis macrochirus (Bluegill))
	0.00155-0.00293 mg/l (Pimephales promelas)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 7)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 6)

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1210
UN proper shipping name DOT, ADR, IATA IMDG	Printing ink PRINTING INK, MARINE POLLUTANT
Transport hazard class(es)	
DOT	
TICAMOUNTE TAZARI	
Class Label	3 Flammable liquids 3
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: Silver Yes (DOT)
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30 E E C D
EMS Number: Stowage Category	F-E,S-D A

(Contd. on page 8)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 7) · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 60 L · Quantity limitations On cargo aircraft only: 220 L $\cdot ADR$ · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L Code: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN ''Model Regulation'': UN 1210 PRINTING INK, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-22-4 Silver

· TSCA (Toxic Substances Control Act):

All ingredients are listed or comply with TSCA regulations.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

7440-22-4 | Silver

D

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

7440-22-4 Silver

(Contd. on page 9)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 8)

· New Jersey State Right To Know List

7440-22-4 Silver

· Pennsylvania Hazardous Substances List

7440-22-4 Silver

- · California SCAQMD Rule 443.1 VOC's: No information available.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS07

GHS09

· Signal word Warning

· Hazard-determining components of labeling:

n-Butyl acetate

· Hazard statements

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P370+P378 In case of fire: Use for extinction: Carbon dioxide. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

· Other regulations, limitations and prohibitive regulations

RoHS 2 2011/65/EU along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

(Contd. on page 10)



Printing date 1/24/2017 Reviewed on 1/24/2017

Trade name: AG-610 Silver Conductive Ink

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr. Cole
- · Revision History: New SDS, Rev. 1 1/24/2017
- · Date of preparation / last revision 1/24/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $NFPA: National\ Fire\ Protection\ Association\ (USA)$

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids, Hazard Category 3

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

-US