

Printing date 01/27/2017

Reviewed on 01/27/2017

1 Identification of the substance/mixture and of the company


- · Product identifier
- · Trade name: AG-798 Silver Conductive Ink
- · Application of the substance / the mixture Functional electronic screen printing ink
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Applied Ink Solutions 17 Hampshire Drive, Unit 8 Hudson, NH 03051 USA

- Information department: Product Safety Email: sales@appliedinksolutions.com
- Emergency telephone number: Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887 Applied Ink Solutions : 603-595-6221

2 Hazard(s) identification

· Classification of the substance or mixture



Aquatic Acute 1H400 Very toxic to aquatic life.Aquatic Chronic 1H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

 Hazard-determining components of labeling: Phenoxy Resin gamma-Butyrolactone
 Hazard statements H332 Harmful if inhaled.

(Contd. on page 2)

[–] US

Mapplied Ink Solutions

Printing date 01/27/2017

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

	(Contd. of page 1)
H315 Causes sk	
	prious eye irritation.
	e an allergic skin reaction.
	e drowsiness or dizziness.
H400 Very toxic	
	c to aquatic life with long lasting effects.
• Precautionary s	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· Classification s	
· NFPÅ ratings (
▲ Ŭ,	
	Iealth = 1
	iire = 1
	Peactivity = 0
· HMIS-ratings ((scale 0 - 4)
HEALTH 1	
	Health = 1
	Fire = 1
REACTIVITY 0	Reactivity = 0
• Other hazards	
	and vPvB assessment
· PBT: Not applie	
• vPvB: Not appli	
3 Composition	/information on ingredients
. Chomical chara	acterization: Mixtures
	ixture of the substances listed below with nonhazardous additions.
· Description. Mi	Mare of the substances asted below with nonnuzurabus additions.

 • Dangerous components:
 40-60%

 7440-22-4
 Silver
 40-60%

 ③ Aquatic Acute 1, H400; Aquatic Chronic 1, H410
 25-50%

 96-48-0
 gamma-Butyrolactone
 25-50%

 ④ Acute Tox. 4, H302; Eye Irrit. 2A, H319; STOT SE 3, H336
 5-15%

 ● Phenoxy Resin
 5-15%

 ④ Aquatic Chronic 2, H411; ④ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317

(Contd. on page 3)

US



Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing: Do not induce vomiting; immediately call a doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
Ensure adequate ventilation	
· Environmental precautions:	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
• PAC-1:	
7440-22-4 Silver	0.3 mg/m3
	(Could on mana

(Contd. on page 4)

US



Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

96-48-0	gamma-Butyrolactone	(Contd. of page 3.6 mg/m3
	Phenoxy Resin	90 mg/m3
PAC-2:		
7440-22-4	Silver	170 mg/m3
96-48-0	gamma-Butyrolactone	39 mg/m3
	Phenoxy Resin	990 mg/m3
PAC-3:		
7440-22-4	Silver	990 mg/m3
96-48-0	gamma-Butyrolactone	310 mg/m3
	Phenoxy Resin	5,900 mg/m2

7 Handling and storage

· Handling:

 Precautions for safe handling Ensure good ventilation/exhaust at the workplace.
 Prevent formation of aerosols.
 Information about protection against explosions and fires: Protect against electrostatic charges.

No special measures required.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.

• Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials.

- Further information about storage conditions:
- Keep container well-sealed in cool, dry location.
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- \cdot General protective and hygienic measures:
- Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

(Contd. on page 5)

[–] US



Printing date 01/27/2017

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

(Contd. of page 4)

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. • Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- · Penetration time of glove material Contact glove manufacture for break-through time.
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Appearance: Form:	Thick liquid	
Color:	Silver-colored	
Odor:	Sweet	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	205 °C (401 °F)	
Flash point:	100 °C (212 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	445 °C (833 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	2.7 Vol %	
Upper:	15.6 Vol %	
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	> 1 hPa (> 1 mm Hg)	
Density:	2,43 gm/cm ³ ; 20.32 lbs/gal	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	1.6-2.3 (BuAc=1)	
Solubility in / Miscibility with		
Water:	Water miscible No	



Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

		(Contd. of page
· Partition coefficient (n-octand	p l/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	31.4 %	
VOC content:	31.4 %	
Solids content:	68.5 %+/- 2%	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability Stable under normal use conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid
- *Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.*
- Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

96-48-0 gamma-Butyrolactone

		1540 mg/kg (Rat)
	LD50	5000 mg/kg (gui)
Inhalative	LC50/4 h	>5.1 mg/l (Rat)
D1		

Phenoxy Resin Oral LD50

		30000 mg/kg (Rat)
Dermal	LD50	>1200 mg/kg (Rat)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Harmful
- Irritant
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

96-48-0 gamma-Butyrolactone





Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

• Aquatic toxicity.	:	
96-48-0 gamma-	-Butyrolactone	
LC50/96 h	>220 - <460 mg/l (golden orfe)	
EC50/48 h	>500 mg/l (daphnia magna)	
EC50/72 h	360 mg/l (green algae)	
EC50/17 h	>10000 mg/l (bacterium)	
7440-22-4 Silver	r	
I 050/061 /		

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

• *Persistence and degradability* No further relevant information available.

· Behavior in environmental systems:

• *Bioaccumulative potential* No further relevant information available.

- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Harmful to aquatic organisms
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)



Printing date 01/27/2017

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

(Contd. of page 7)

US

UN-Number	
DOT, ADR, IMDG, IATA	UN3082
UN proper shipping name	
DOT, ADR	Environmentally hazardous substances, liquid, n.o.s. (Silver, 4,4
MDC	Isopropylidenediphenol- Epichlorohydrin Copolymer)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydria
	Copolymer), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID
	N.O.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydri
	Copolymer)
Transport hazard class(es)	
DOT, ADR, IMDG, IATA	
A	
Allh,	
8	
₩ Class	
Class Label	9 Miscellaneous dangerous substances and articles 9
	,
Packing group DOT, ADR, IMDG, IATA	111
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: Silver Yes (DOT)
-	
Special precautions for user Danger code (Kemler):	Warning: Miscellaneous dangerous substances and articles 90
Danger code (Kemier): EMS Number:	90 F-A,S-F
Stowage Category	A
Transport in bulk according to Annex.	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Ouantity limitations	On passenger aircraft/rail: No limit
Quunny unumons	On passenger aircraft only: No limit On cargo aircraft only: No limit
4DD	
ADR Excepted quantities (EQ)	Code: El
Excepted quantants (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml



Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

(Contd. of page 8)

· UN ''Model Regulation'':

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (SILVER, 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN COPOLYMER), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-22-4 Silver

· TSCA (Toxic Substances Control Act):

All ingredients are listed or comply with TSCA regulations.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-22-4 Silver

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

7440-22-4 Silver

· New Jersey State Right To Know List

7440-22-4 Silver

96-48-0 gamma-Butyrolactone

· Pennsylvania Hazardous Substances List

7440-22-4 Silver

96-48-0 gamma-Butyrolactone

· California SCAOMD Rule 443.1 VOC's: No information available.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

- US

D



,			Page 10/11
Applied Inl	 Solutions A DIVISION OF MICROCHEM 	Safety Data Sheet acc. to OSHA HCS	
Printing date 01/27/2	2017		Reviewed on 01/27/2017
Trade name: AG-79	8 Silver Conductiv	e Ink	
			(Contd. of page 9)
• Hazard pictogra	ms		(00,1141,0) page >)
	13		
	-		
GHS07 GHS	.09		
	0,7		
· Signal word Wa	rning		
• Hazard-determi	ning components o	of labeling:	
Phenoxy Resin		<i>y</i>	
gamma-Butyrola	ictone		
• Hazard statemer			
H332 Harmful if			
H315 Causes ski			
	rious eye irritation.		
	e an allergic skin re		
	e drowsiness or dizz	ziness.	
H400 Very toxic		a long lasting officies	
· Precautionary s		n long lasting effects.	
P261		g dust/fume/gas/mist/vapors/spray	
P280		e gloves/protective clothing/eye protection	ction/face protection
P273		o the environment.	enonsfuce protection.
P301+P310		ED: Immediately call a POISON CEN	TER/ doctor.
			ninutes. Remove contact lenses, if present
		Continue rinsing.	, , , , , , , , , , , , , , , , , , ,
P304+P340		Remove person to fresh air and keep o	comfortable for breathing.
P333+P313	If skin irritation	n or rash occurs: Get medical advice/	(attention.
P337+P313		persists: Get medical advice/attention	n.
P302+P352		Vash with plenty of soap and water.	
P403+P233		ventilated place. Keep container tight	
P501	Dispose of con regulations.	itents/container in accordance wit	h local/regional/national/international
· National regula	tions:		
• Other regulation	is, limitations and	prohibitive regulations	
		EU Directive 2022/19/EU – Waste	from Electrical and Electronic
Equipment (WE			
		lo not exceed the amount of allow	able levels concerning: Cadmium(Cd);
			ninated Biphenyls (PBB's) as bromide;
Polybrominated	Diphenyl Ethers (F	PBDEs) as bromide, decaBDE.	

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern(SVHC): This product does not contain substances on the SVHC list. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

- US



Printing date 01/27/2017

Reviewed on 01/27/2017

Trade name: AG-798 Silver Conductive Ink

	(Contd. of page 1
Department issuing SDS: Product safety department	
Contact: Mr. Cole	
Revision History: New SDS	
Date of preparation / last revision 01/27/2017 / -	
Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement	concerning the Internation
Carriage of Dangerous Goods by Road)	-
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	