Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2019 Reviewed on 06/04/2019

1 Identification

- · Product identifier
- · Trade name: WB-1078-1 Water-Based Silver Conductive Ink
- · Application of the substance / the mixture Film coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Applied Ink Solutions 200 Flanders Road Westborough, MA 01581 USA
- · Information department:

Product Safety

Email: sales@appliedinksolutions.com

· Emergency telephone number:

Applied Ink Solutions : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07

GHS08

GHS09

· Signal word Danger

(Contd. on page 2)



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 1)

· Hazard-determining components of labeling:

Urethane acrylate oligomer

N-methyl-2-pyrrolidinone

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7440-22-4	Silver	60-80%
	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

	Urethane acrylate oligomer	10-25
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	
872-50-4	72-50-4 N-methyl-2-pyrrolidinone	
	Acute Tox. 3, H331; & Repr. 1B, H360; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227	
	Components:	
		1-5%
· Additional	Components:	1-5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

 \cdot After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 3)

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1</i> :		
7440-22-4	Silver	0.3 mg/m ³
872-50-4	N-methyl-2-pyrrolidinone	30 ppm
577-11-7	Dioctyl sodium sulfosuccinate	5.7 mg/m ²
PAC-2:		
7440-22-4	Silver	170 mg/m ²
872-50-4	N-methyl-2-pyrrolidinone	32 ppm
577-11-7	Dioctyl sodium sulfosuccinate	63 mg/m3
PAC-3:		
7440-22-4	Silver	990 mg/m ²
872-50-4	N-methyl-2-pyrrolidinone	190 ppm
577-11-7	Dioctyl sodium sulfosuccinate	380 mg/m ²

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 4)

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

872-50-4 N-methyl-2-pyrrolidinone

WEEL Long-term value: 10 ppm

Skin

· Ingredients with biological limit values:

872-50-4 N-methyl-2-pyrrolidinone

BEI 100 mg/L

Medium: urine Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Silver-colored

· Odor: Mild

· Odor threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 6)



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

	(Con	td. of page
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100°C (212°F)	
Flash point:	94 °C (201.2 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	See other information	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	1.6-2.3 (BuAc=1)	
Solubility in / Miscibility with		
Water:	Water miscible No	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	2.3 %	
Water:	16.7 %	
VOC content:	2.3 %	
Solids content:	68.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability

Stable under normal use conditions

Stable

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 7)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN3082
· UN proper shipping name	
· DOT, ADR	Environmentally hazardous substances, liquid, n.o.s. (Silver)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIL N.O.S. (Silver), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID
	N.O.S. (Silver)
· Transport hazard class(es)	
· DOT, ADR, IMDG, IATA	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group	
· DOT, ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: Silver
· Marine pollutant:	Yes (DOT)
· Special precautions for user · Danger code (Kemler):	Warning: Miscellaneous dangerous substances and articles 90
· EMS Number:	F-A,S-F
· Stowage Category	A
· Transport in bulk according to Annex I	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: No limit
	On cargo aircraft only: No limit
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· <i>IMDG</i>	
· Limited quantities (LQ)	5L

(Contd. on page 9)



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

	(Contd. of page 8)
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (SILVER), 9, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture

· Section 355 (extremely hazardous substances):		
None of the ingredients are listed.		
· Section 313 (Specific toxic chemical listings):		
7440-22-4	Silver	
872-50-4	N-methyl-2-pyrrolidinone	

- · TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidinone

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
7440-22-4 Silver	D)

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

7440-22-4 Silver

872-50-4 N-methyl-2-pyrrolidinone

· New Jersey State Right To Know List

7440-22-4 Silver

872-50-4 N-methyl-2-pyrrolidinone

· Pennsylvania Hazardous Substances List

7440-22-4 Silver

872-50-4 N-methyl-2-pyrrolidinone

· California SCAQMD Rule 443.1 VOC's: No information available.

(Contd. on page 10)



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 9)

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Urethane acrylate oligomer N-methyl-2-pyrrolidinone

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

· Other regulations, limitations and prohibitive regulations

RoHS (EU)2015/863 along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Mercury (Hg); Lead (Pb); Hexavalent chromium (Cr6+); Polybrominated biphenyls (PBB); Polybrominated diphenyl ethers (PBDE); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DBP); Diisobutyl phthalate (DIBP)

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the **Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.**

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product contains a substance on the SVHC list: CAS 872-50-4 1-Methyl-2-pyrrolidone.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: WB-1078-1 Water-Based Silver Conductive Ink

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr. Cole
- · Revision History: New SDS
- · Date of preparation / last revision 06/04/2019 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

us ·