

1 Identification of the substance/mixture and of the company

· **Product identifier**

· **Trade name:** XM-1089 Carbon Resistive Ink

· **Application of the substance / the mixture** *Functional electronic carbon printing ink*

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Applied Ink Solutions
 17 Hampshire Drive, Unit 8
 Hudson, NH 03051
 USA

· **Information department:**

Product Safety
 Email: sales@appliedinksolutions.com

· **Emergency telephone number:**

Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887
 Applied Ink Solutions : 603-595-6221

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Flam. Liq. 4 H227 Combustible liquid.

· **Label elements**

· **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

gamma-Butyrolactone

Carbon black

Quartz (SiO₂)

· **Hazard statements**

H227 Combustible liquid.

H332 Harmful if inhaled.

(Contd. on page 2)

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 1)

*H319 Causes serious eye irritation.**H350 May cause cancer.**H336 May cause drowsiness or dizziness.*
· Precautionary statements
*P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.**P261 Avoid breathing dust/fume/gas/mist/vapors/spray**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.**P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.**P370+P378 In case of fire: Use for extinction: Carbon dioxide.**P302+P352 IF ON SKIN: Wash with plenty of soap and water.**P403+P233 Store in a well-ventilated place. Keep container tightly closed.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = 1

Fire = 2

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients
· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

96-48-0	gamma-Butyrolactone	Acute Tox. 4, H302; Eye Irrit. 2A, H319; STOT SE 3, H336	25-50%
1333-86-4	Carbon black	Carc. 2, H351	5-15%
627-93-0	Dimethyl adipate	Aquatic Acute 3, H402	5-15%
106-65-0	Methyl succinate	Flam. Liq. 4, H227	5-15%
14808-60-7	Quartz (SiO ₂)	Carc. 1A, H350	<1%

· Additional Components:

7782-42-5	Graphite	10-25%
1119-40-0	Dimethyl glutarate	10-25%

(Contd. on page 3)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 2)

Proprietary binder

10-25%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Remove breathing apparatus only after contaminated clothing have been completely removed.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
 Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
 Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.
- **After swallowing:** Do not induce vomiting; immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 Alcohol resistant foam
 Fire-extinguishing powder
 ABC powder
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to Section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 4)

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 3)

· Protective Action Criteria for Chemicals
· PAC-1:

96-48-0	gamma-Butyrolactone	3.6 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
106-65-0	Methyl succinate	2.5 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

· PAC-2:

96-48-0	gamma-Butyrolactone	39 mg/m ³
1333-86-4	Carbon black	99 mg/m ³
106-65-0	Methyl succinate	28 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³

· PAC-3:

96-48-0	gamma-Butyrolactone	310 mg/m ³
1333-86-4	Carbon black	590 mg/m ³
106-65-0	Methyl succinate	170 ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities
· Storage:

· Requirements to be met by storerooms and containers: No special requirements.

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters
· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 4)

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

14808-60-7 Quartz (SiO₂)

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material** Contact glove manufacture for break-through time.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Thick liquid

Color: Black

· **Odor:** Sweet

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 6)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 5)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	96 °C (205 °F)
· Flash point:	90 °C (194 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	445 °C (833 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	2.7 Vol %
Upper:	15.6 Vol %
· Vapor pressure at 20 °C (68 °F):	8.3 hPa (6 mm Hg)
· Density at 20 °C (68 °F):	1.34797 g/cm ³ (11.249 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	1.6-2.3 (BuAc=1)
· Solubility in / Miscibility with Water:	Water miscible No
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	33.6 %
VOC content:	33.6 %
Solids content:	41.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal use conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
 Heat, flames and sparks. Extremes of temperature and direct sunlight.
 Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Contd. on page 7)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

96-48-0 gamma-Butyrolactone

Oral	LD50	1540 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (gui)
Inhalative	LC50/4 h	>5.1 mg/l (Rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

96-48-0	gamma-Butyrolactone	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO2)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO2)	K
------------	---------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12 Ecological information

- **Toxicity**

· **Aquatic toxicity:**

96-48-0 gamma-Butyrolactone

LC50/96 h	>220 - <460 mg/l (golden orfe)
EC50/48 h	>500 mg/l (daphnia magna)
EC50/72 h	360 mg/l (green algae)
EC50/17 h	>10000 mg/l (bacterium)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 8)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.
Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Not Regulated
· UN proper shipping name	
· DOT, ADR, ADN, IMDG, IATA	Not Regulated
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not Regulated
· Packing group	
· DOT, ADR, IMDG, IATA	Not Regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Not Regulated

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed or comply with TSCA regulations.
· Proposition 65
· Chemicals known to cause cancer:
1333-86-4 Carbon black
14808-60-7 Quartz (SiO ₂)

(Contd. on page 9)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 8)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **New Jersey State Right To Know List**

96-48-0	gamma-Butyrolactone
1119-40-0	Dimethyl glutarate
627-93-0	Dimethyl adipate

· **Pennsylvania Hazardous Substances List**

96-48-0	gamma-Butyrolactone
1119-40-0	Dimethyl glutarate
627-93-0	Dimethyl adipate

· **California SCAQMD Rule 443.1 VOC's:** No information available.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

gamma-Butyrolactone

Carbon black

Quartz (SiO₂)

· **Hazard statements**

H227 Combustible liquid.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 10)

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 9)

- P301+P310** IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P305+P351+P338** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304+P340** IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P333+P313** If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313** If eye irritation persists: Get medical advice/attention.
- P370+P378** In case of fire: Use for extinction: Alcohol resistant foam.
- P370+P378** In case of fire: Use for extinction: Fire-extinguishing powder.
- P370+P378** In case of fire: Use for extinction: Carbon dioxide.
- P302+P352** IF ON SKIN: Wash with plenty of soap and water.
- P403+P233** Store in a well-ventilated place. Keep container tightly closed.
- P501** Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Other regulations, limitations and prohibitive regulations**

RoHS 2 2011/65/EU along with EU Directive 2012/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the **Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.**

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern(SVHC): This product does not contain substances on the SVHC list.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** Mr. Cole

- **Revision History:** New SDS

- **Date of preparation / last revision** 12/22/2016 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 11)

Printing date 12/22/2016

Reviewed on 12/22/2016

Trade name: XM-1089 Carbon Resistive Ink

(Contd. of page 10)

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 1A: Carcinogenicity – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

US