

Printing date 11/06/2019 Reviewed on 11/06/2019

# 1 Identification

- · Product identifier
- · Trade name: UV-2530 UV Curable Matte Dielectric Blue, Clear, Green
- · Application of the substance / the mixture Functional Electronic Insulating Ink
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Applied Ink Solutions

200 Flanders Road

Westborough, MA 01581

USA

· Information department:

**Product Safety** 

Email: productsafety@kayakuAM.com

· Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



### GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Flam. Liq. 4 H227 Combustible liquid. Aquatic Acute 2 H401 Toxic to aquatic life.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07

GHS08

GHS09



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 1)

- · Signal word Warning
- · Hazard-determining components of labeling:

Dipentaerythritol pentaacrylate esters

· Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

*P273* Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

*P301+P310* If swallowed: Immediately call a poison center/doctor.

*P302+P352* If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

*P370+P378 In case of fire: Use for extinction: Carbon dioxide.* 

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 2) · Dangerous components: Urethane acrylate oligomer 40-60% 🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317 60506-81-2 Dipentaerythritol pentaacrylate esters 25-50% 🕠 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227 14807-96-6 Talc (Mg3H2(SiO3)4) 10-25% & Carc. 2, H351 24650-42-8 2,2-dimethoxy-2-phenylacetophenone 1-5% 🔖 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acrylic leveling agent 1-5% 🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Proprietary Dye <1% 🗘 Eye Irrit. 2A, H319; Skin Sens. 1A, H317 119-61-9 Benzophenone <1% & Carc. 2, H351; 🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

## 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air and to be sure call for a doctor.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

*Fire-extinguishing powder* 

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water spray
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

(Contd. on page 4)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 3)

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respirator available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Store away from reducing agents.

Store away from oxidizing agents.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

(Contd. on page 5)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 4)

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

0 D1 · 1		7 . 7		
9 Physical	and	rhemical	nro	nørtiøs
/ I Trysteut	ullu	<i>member</i>	$\rho T U$	

· Information on basic physical and o	chemical properties
· General Information	
· Appearance:	
Form:	Thick liquid
Color:	Blue, Clear, Green
· Odor:	Sweet
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	93 °C (199.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.22 g/cm³ (10.1809 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	1.6-2.3 (BuAc=1)
· Solubility in / Miscibility with	
Water:	Water miscible No

(Contd. on page 6)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

		(Contd. of page 5
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- $\cdot \textit{Sensitization: Sensitization possible through skin contact.}$
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
14807-96-6	Talc (Mg3H2(SiO3)4)	2B
119-61-9	Benzophenone	2 <i>B</i>
· NTP (Nation	nal Toxicology Program)	
None of the	ingredients are listed.	
· OSHA-Ca (	Occupational Safety & Health Administration)	
None of the	ingredients are listed.	



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 6)

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 24650-42-8 2,2-dimethoxy-2-phenylacetophenone

EC50/48 h 26 mg/l (daphnia magna)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN3082
· UN proper shipping name	
· DOT, ADR	Environmentally hazardous substances, liquid, n.o.s. (2,
	dimethoxy-2-phenylacetophenone, Benzophenone)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI
	N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone
	MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI
	N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone)

(Contd. on page 8,



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

	(Contd. of page
· Transport hazard class(es)	
DOT, ADR, IMDG, IATA	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: 2, dimethoxy-2-phenylacetophenone
Marine pollutant:	Yes (DOT)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Danger code (Kemler):	90
EMS Number:	F- $A$ , $S$ - $F$
Stowage Category	A
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (2,2-DIMETHOXY-2-PHENYLACETOPHENON BENZOPHENONE), 9, III

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

(Contd. on page 9)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 8)

•	Pro	position	65

#### · Chemicals known to cause cancer:

119-61-9 Benzophenone

### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

#### · Carcinogenic categories

### · EPA (Environmental Protection Agency)

None of the ingredients are listed.

## · TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Talc (Mg3H2(SiO3)4)

*A4* 

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

#### · New Jersey State Right To Know List

119-61-9 Benzophenone

#### · Pennsylvania Hazardous Substances List

119-61-9 Benzophenone

- · California SCAQMD Rule 443.1 VOC's: No information available.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07

GHS08 GHS09

#### · Signal word Warning

## · Hazard-determining components of labeling:

Dipentaerythritol pentaacrylate esters

#### · Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

*H411 Toxic to aquatic life with long lasting effects.* 

## · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 10)



Printing date 11/06/2019 Reviewed on 11/06/2019

Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 9)

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · National regulations:

### · Other regulations, limitations and prohibitive regulations

RoHS (EU)2015/863 along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Mercury (Hg); Lead (Pb); Hexavalent chromium (Cr6+); Polybrominated biphenyls (PBB); Polybrominated diphenyl ethers (PBDE); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DBP); Diisobutyl phthalate (DIBP).

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product does not contain substances on the SVHC list.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- · Date of preparation / last revision 11/06/2019 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 11)



Printing date 11/06/2019 Reviewed on 11/06/2019

## Trade name: UV-2530 UV Curable Matte Dielectric - Blue, Clear, Green

(Contd. of page 10)

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

– U