

# Printing date 03/06/2017

### Reviewed on 03/06/2017

## 1 Identification of the substance/mixture and of the company

- · Product identifier
- Trade name: EP-1100 Single Component Silver Conductive Epoxy
- · Application of the substance / the mixture Single Component Silver Conductive Epoxy

Safety Data Sheet

acc. to OSHA HCS


• Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Applied Ink Solutions 17 Hampshire Drive, Unit 8 Hudson, NH 03051 USA

- Information department: Product Safety Email: sales@appliedinksolutions.com
- Emergency telephone number: Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887 Applied Ink Solutions : 603-595-6221

## 2 Hazard(s) identification

· Classification of the substance or mixture



Aquatic Acute 1H400Very toxic to aquatic life.Aquatic Chronic 1H410Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Flam. Liq. 4	H227 Combustible liquid.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Warning

Hazard-determining components of labeling: Phenoxy Resin Oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Hazard statements H227 Combustible liquid. H315 Causes skin irritation.

(Contd. on page 2)



Printing date 03/06/2017

## Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/06/2017

### Trade name: EP-1100 Single Component Silver Conductive Epoxy

	(Contd. of page 1)
	rious eye irritation.
	e an allergic skin reaction.
H400 Very toxic	
	to aquatic life with long lasting effects.
· Precautionary s	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification sy	
· NFPA ratings (s	
Н	Tealth = 1
	ire = 2
	eactivity = 0
· HMIS-ratings (	scale 0 - 4)
FIRE 2	Health = 1 Fire = 2 Reactivity = 0
	Acachivity = 0
• Other hazards	
	and vPvB assessment
• <b>PBT:</b> Not applic	
• <b>vPvB:</b> Not appli	cable.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

7440-22-4		75-100%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1
	Phenoxy Resin	5-15%
	Aquatic Chronic 2, H411; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	-
34590-94-8	Dipropylene glycol methyl ether	5-15%
	Flam. Liq. 4, H227	1

US —



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

	(Co	ntd. of page 2)
	Aliphatic amines	1-5%
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs	1-5%
	🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Phenolic Resin	1-5%
	🚯 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:
- Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

### 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources
 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

(Contd. on page 4)



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name	: EP-1100	) Single Component	Silver	Conductive	Epoxy
------------	-----------	--------------------	--------	------------	-------

		(Contd. of page
Reference to	o other sections	
	7 for information on safe handling.	
	8 for information on personal protection equipment.	
	13 for disposal information.	
Protective A	ction Criteria for Chemicals	
PAC-1:		
7440-22-4	Silver	0.3 mg/m.
	Phenoxy Resin	90 mg/m3
34590-94-8	Dipropylene glycol methyl ether	150 ppm
PAC-2:		
7440-22-4	Silver	170 mg/m.
	Phenoxy Resin	990 mg/m.
34590-94-8	Dipropylene glycol methyl ether	1700* ppr
PAC-3:		
7440-22-4	Silver	990 mg/m3
	Phenoxy Resin	5,900 mg/m.
34590-94-8	Dipropylene glycol methyl ether	9900** ppm

### 7 Handling and storage

#### · Handling:

- *Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.*
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- $\cdot$  Information about storage in one common storage facility:
- Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials.
- · Further information about storage conditions:
- Keep container well-sealed in cool, dry location.
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

<sup>-</sup> US -



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

34590-94-8 Dipropylene glycol methyl ether         PEL       Long-term value: 600 mg/m³, 100 ppm         Skin       REL         Short-term value: 600 mg/m³, 150 ppm         Long-term value: 600 mg/m³, 150 ppm         Skin         TLV       Short-term value: 606 mg/m³, 100 ppm         Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from food and beverages.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Avoid contact with the eyes and skin.         Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protective gloves         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:         Tightly sealed goggles	2 15 01	(Contd. of page
Skin       Skin         REL       Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin         TLV       Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from food and beverages.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Avoid contact with the eyes and skin.         Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:		
REL       Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin         TLV       Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands:         Vivo       Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin TLV Short-term value: 909 mg/m <sup>3</sup> , 150 ppm Long-term value: 606 mg/m <sup>3</sup> , 100 ppm Skin Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Skin       Skin         TLV       Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective equipment:         General protective and hygienic measures:         Keep away from food and beverages.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Avoid contact with the eyes and skin.         Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protection of hands:         Virol         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:		
TLV       Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from food and beverages.         Immediately remove all solied and contaminated clothing.         Wash hands before breaks and at the end of work.         Avoid contact with the eyes and skin.         Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protection of hands:         Vivo         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:		
Long-term value: 606 mg/m <sup>3</sup> , 100 ppm Skin Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Skin         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from food and beverages.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Avoid contact with the eyes and skin.         Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:		
Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	Addit	ional information: The lists that were valid during the creation were used as basis.
General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	Expo	sure controls
Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. <b>Respiratory equipment:</b> In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. <b>Protection of hands:</b> Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. <b>Respiratory equipment:</b> In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. <b>Protection of hands:</b> <i>Protective gloves</i> The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
<ul> <li>Wash hands before breaks and at the end of work.</li> <li>Avoid contact with the eyes and skin.</li> <li><b>Respiratory equipment:</b></li> <li>In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.</li> <li><b>Protection of hands:</b></li> <li><i>Protective gloves</i></li> <li>The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.</li> <li><b>Material of gloves</b> Nitrile rubber, NBR</li> <li><b>Penetration time of glove material</b> Contact glove manufacture for break-through time.</li> <li><b>Eye protection:</b></li> </ul>		
Avoid contact with the eyes and skin. <b>Respiratory equipment:</b> In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. <b>Protection of hands:</b>		
Respiratory equipment:         In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.         Protection of hands:         Image: Protective gloves         Protective gloves         The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.         Material of gloves Nitrile rubber, NBR         Penetration time of glove material Contact glove manufacture for break-through time.         Eye protection:		
In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. <b>Protection of hands:</b>		•
Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	-	
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	11000	such of numes.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	II.	
Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	6005	Protective gloves
Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	V	
Material of gloves Nitrile rubber, NBR Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:	The g	love material has to be impermeable and resistant to the product/ the substance/ the preparation.
Penetration time of glove material Contact glove manufacture for break-through time. Eye protection:		
Eye protection:		
Tightly sealed goggles		
Tightly sealed goggles		
Tightiy sedied goggles		Tishdu saslad sasalas
		John Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
· Appearance:		
Form: Color:	Thick Paste Silver-colored	
· Odor:	Strong	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	190 °C (374 °F)	
Flash point:	75 °C (167 °F)	



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

		(Contd. of page
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density:	3.08 gm/cm <sup>3</sup> ; 25.64 lbs/gal	
Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	1.6-2.3 (BuAc=1)	
Solubility in / Miscibility with		
Water:	Water miscible No	
Partition coefficient (n-octanol/wat	t <b>er):</b> Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	5.7 %	
VOC content:	5.7 %	
Solids content:	94.3 %	
• Other information	No further relevant information available.	

### 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability Stable under normal use conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

### 11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

### · LD/LC50 values that are relevant for classification:

Phenoxy Resin

*Oral LD50 30000 mg/kg* (*Rat*)

(Contd. on page 7)

US -



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

(Contd. of page 6)

Dermal LD50 >1200 mg/kg (Rat)

· Primary irritant effect:

 $\cdot$  on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: Sensitization possible through skin contact.

• Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

### 12 Ecological information

· Toxicity

· Aquatic toxicity:

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

· Persistence and degradability No further relevant information available.

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Harmful to aquatic organisms
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

#### • Waste treatment methods

· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)

<sup>-</sup>US -



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

(Contd. of page 7)

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

3082 ironmentally hazardous substances, liquid, n.o.s. (Silver, 4,4 oropylidenediphenol- Epichlorohydrin Copolymer) VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID O.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydrin vIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID O.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydrin oolymer) 'iscellaneous dangerous substances and articles duct contains environmentally hazardous substances: Silver
propylidenediphenol- Epichlorohydrin Copolymer) VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID D.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydri VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID D.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydri polymer)
bropylidenediphenol- Epichlorohydrin Copolymer) VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID D.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydrin VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID D.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydrin bolymer)
VIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID D.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydri polymer) (iscellaneous dangerous substances and articles duct contains environmentally hazardous substances: Silver
duct contains environmentally hazardous substances: Silver
duct contains environmentally hazardous substances: Silver
duct contains environmentally hazardous substances: Silver
duct contains environmentally hazardous substances: Silver
duct contains environmentally hazardous substances: Silver
·
· ·
(DOT)
rning: Miscellaneous dangerous substances and articles
, <i>S</i> - <i>F</i>
applicable.
passenger aircraft/rail: No limit cargo aircraft only: No limit
le: E1 ximum net quantity per inner packaging: 30 ml ximum net quantity per outer packaging: 1000 ml

US -



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

	(Contd. of page 8)
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (SILVER, 4,4'-ISOPROPYLIDENEDIPHENOL- EPICHLOROHYDRIN COPOLYMER), 9, III

## 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-22-4 Silver

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations. • Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

 $\cdot$  Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-22-4 Silver

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

7440-22-4 Silver

34590-94-8 Dipropylene glycol methyl ether

· New Jersey State Right To Know List

7440-22-4 Silver

34590-94-8 Dipropylene glycol methyl ether

· Pennsylvania Hazardous Substances List

7440-22-4 Silver

34590-94-8 Dipropylene glycol methyl ether

· California SCAQMD Rule 443.1 VOC's: No information available.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

D



Printing date 03/06/2017

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/06/2017

iting date 03/06/	2017 Reviewed on 03/06/201
de name: EP-11	00 Single Component Silver Conductive Epoxy
Hazard pictogra	(Contd. of page
IIuzuru piciogri	ins
<u><!-- -->&lt;ĭ</u>	
$\sim$ $\sim$	
GHS07 GHS	509
Signal word Wa	rning
Hazard-determi	ning components of labeling:
Phenoxy Resin	
	(C12-14-alkyloxy)methyl] derivs
Hazard stateme	
H227 Combusti	
H315 Causes sk	
	rious eye irritation.
	e an allergic skin reaction.
H400 Very toxic	
	to aquatic life with long lasting effects.
Precautionary s	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation
	regulations.
National regula	tions:
04 14	ns, limitations and prohibitive regulations

RoHS 2 2011/65/EU along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmiu (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the **Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.** 

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern(SVHC): This product does not contain substances on the SVHC list. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

US



Printing date 03/06/2017

Reviewed on 03/06/2017

Trade name: EP-1100 Single Component Silver Conductive Epoxy

(Contd. of page 10)

	his information is based on our present knowledge. However, this shall not constitute a guarantee for a pecific product features and shall not establish a legally valid contractual relationship.
-	epartment issuing SDS: Product safety department
	ontact: Mr. Cole
Re	evision History: New SDS
	ate of preparation / last revision 03/06/2017 / -
	bbreviations and acronyms:
	DR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internatio
Ca	urriage of Dangerous Goods by Road)
IM	IDG: International Maritime Code for Dangerous Goods
	OT: US Department of Transportation
	TA: International Air Transport Association
	CGIH: American Conference of Governmental Industrial Hygienists
	NECS: European Inventory of Existing Commercial Chemical Substances
	INCS: European List of Notified Chemical Substances
	AS: Chemical Abstracts Service (division of the American Chemical Society)
	FPA: National Fire Protection Association (USA)
	MIS: Hazardous Materials Identification System (USA) DC: Volatile Organic Compounds (USA, EU)
	C: Volatile Organic Compounds (OSA, EO) C50: Lethal concentration, 50 percent
	D50: Lethal concentration, 50 percent
	37: Persistent, Bioaccumulative and Toxic
	vB: very Persistent and very Bioaccumulative
	OSH: National Institute for Occupational Safety
	5HA: Occupational Safety & Health
	V: Threshold Limit Value
PE	EL: Permissible Exposure Limit
RE	EL: Recommended Exposure Limit
Fla	am. Liq. 4: Flammable liquids – Category 4
Ski	in Irrit. 2: Skin corrosion/irritation – Category 2
Ey	e Irrit. 2A: Serious eye damage/eye irritation – Category 2A
	in Sens. 1: Skin sensitisation – Category 1
	OT SE 3: Specific target organ toxicity (single exposure) – Category 3
40	nuatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1