

1 Identification of the substance/mixture and of the company

- **Product identifier**
- **Trade name:** UV-1053 UV Curable Matte Dielectric
- **Application of the substance / the mixture** *Functional electronic insulating ink*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Applied Ink Solutions
17 Hampshire Drive, Unit 8
Hudson, NH 03051
USA
- **Information department:**
Product Safety
Email: sales@appliedinksolutions.com
- **Emergency telephone number:**
Chemtrec USA Emergency : 800-424-9300
Chemtrec International Emergency : 703-527-3887
Applied Ink Solutions : 603-595-6221

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.
 Flam. Liq. 4 H227 Combustible liquid.
 Aquatic Acute 2 H401 Toxic to aquatic life.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** *Warning*
- **Hazard-determining components of labeling:**
Urethane acrylate oligomer
Talc ($Mg_3H_2(SiO_3)_4$)

(Contd. on page 2)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 1)

Dipentaerythritol pentaacrylate esters

Proprietary Dye

· **Hazard statements**

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 2)

· Dangerous components:

	Urethane acrylate oligomer ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	25-50%
60506-81-2	Dipentaerythritol pentaacrylate esters ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227	25-50%
14807-96-6	Talc (Mg3H2(SiO3)4) ⚠ Carc. 2, H351	10-25%
24650-42-8	2,2-dimethoxy-2-phenylacetophenone ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411	1-5%
	Acrylic leveling agent ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	1-5%
	Proprietary Dye ⚠ Eye Irrit. 2A, H319; Skin Sens. 1A, H317	1-5%
119-61-9	Benzophenone ⚠ Carc. 2, H351; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

4 First-aid measures

· Description of first aid measures
· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Wash skin with soap and water.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

· Information for doctor:
· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

· Extinguishing media
· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters
· Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 3)

Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

119-61-9	Benzophenone	1.5 mg/m ³
546-93-0	Magnesite	45 mg/m ³

· PAC-2:

119-61-9	Benzophenone	90 mg/m ³
546-93-0	Magnesite	260 mg/m ³

· PAC-3:

119-61-9	Benzophenone	310 mg/m ³
546-93-0	Magnesite	1,600 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaust at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**
Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.
- **Further information about storage conditions:**
Keep container well-sealed in cool, dry location.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 4)

At this time, the other constituents have no known exposure limits.

119-61-9 Benzophenone

WEEL Long-term value: 0.5 mg/m³

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves:** Nitrile rubber, NBR
- **Penetration time of glove material:** Contact glove manufacture for break-through time.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Thick liquid
Color:	Green
Odor:	Sweet
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· **Flash point:** 93 °C (199 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

(Contd. on page 6)

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 5)

· Vapor pressure:	Not determined.
· Density:	See other information
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	1.6-2.3 (BuAc=1)
· Solubility in / Miscibility with Water:	Water miscible No
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal use conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	3
119-61-9	Benzophenone	2B
· NTP (National Toxicology Program)		
None of the ingredients are listed.		

(Contd. on page 7)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity
· Aquatic toxicity:
24650-42-8 2,2-dimethoxy-2-phenylacetophenone
EC50/48 h 26 mg/l (daphnia magna)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:
· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:
· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods
· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

· Uncleaned packagings:
· Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number
· DOT, ADR, IMDG, IATA

Not Regulated

· UN proper shipping name
· DOT, ADR, IMDG, IATA

Not Regulated

· Transport hazard class(es)
· DOT, ADR, IMDG, IATA
· Class

Not Regulated

· Packing group
· DOT, ADR, IMDG, IATA

Not Regulated

· Environmental hazards:

Not applicable.

· Special precautions for user

Not applicable.

(Contd. on page 8)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 7)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **UN "Model Regulation":** Not Regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

· **Proposition 65**

· **Chemicals known to cause cancer:**

119-61-9 | Benzophenone

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6 | Talc (Mg3H2(SiO3)4)

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **California SCAQMD Rule 443.1 VOC's:** No information available.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Urethane acrylate oligomer

Talc (Mg3H2(SiO3)4)

Dipentaerythritol pentaacrylate esters

Proprietary Dye

(Contd. on page 9)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 8)

· Hazard statements

- H227 Combustible liquid.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P273 Avoid release to the environment.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
- P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
- P370+P378 In case of fire: Use for extinction: Carbon dioxide.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:**· Other regulations, limitations and prohibitive regulations**

RoHS 2 2011/65/EU along with EU Directive 2002/95/EC – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the **Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.**

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product does not contain substances on the SVHC list.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Mr. Cole

· Revision History: New SDS

· Date of preparation / last revision 06/05/2017/-

(Contd. on page 10)

Printing date 06/05/2017

Reviewed on 06/05/2017

Trade name: UV-1053 UV Curable Matte Dielectric

(Contd. of page 9)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

-US-